

350

T. 25 S., R. 1 W., Willamette Meridian, Oregon

CHAINS

The mean magnetic declination is 19° 30' E.

Dependent Resurvey of a Portion of the East Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

(Restoring the survey by John A. McQuinn,
U. S. Deputy Surveyor, in 1883,
the resurvey by Hezekiah H. Johnson,
U. S. Deputy Surveyor, in 1900,
the resurvey by Levi E. Tallett,
Cadastral Engineer, in 1951,
and the resurvey by Lynn M. Roseberry,
Cadastral Surveyor, in 1957)

Beginning at the cor. of secs. 25 and 36 only, perpetuated
and recorded by Vernon R. Tracy, Deputy County Surveyor,
in 1967, and further perpetuated and recorded by Thomas
E. Shrum, Jr., Registered Engineer No. 4287, in 1975,
monumented with an iron post, 1½ ins. diam., firmly set,
projecting 10 ins. above ground, with brass cap mkd.

T 25 S R 2 W
 $\frac{S 25}{S 36} | WM$
 1975

from which bearing trees mkd. by Johnson

A fir, 50 ins. diam., bears S. 26° E., 31 lks.
dist., with healed blaze.

A white fir, 8 ins. diam., bears S. 25° W., 65
lks. dist., with healed blaze.

A white fir, 8 ins. diam., bears N. 35½° W., 31½
lks. dist., with scribe marks T25S R2W S25 BT
visible on opened blaze. (Record, 27 lks.)

and a bearing tree mkd. by Tracy

A white fir, 8 ins. diam., bears S. 43° W., 46
lks. dist., with scribe marks R2W S36 BT
visible on open blaze.

N. 0° 12' W., on the E. bdy. of sec. 25, marking and
blazing the true line.

Ascend 105 ft. over SW. slope, through heavy timber and
dense undergrowth.

6.90 Ridge, bears N. 80° E. and S. 80° W.; desc. 770 ft. over
NE. slope.

8.00 Gravelled road, 50 lks. wide, bears N. 70° E. and
S. 70° W.

34.90 Creek, 3 lks. wide, course N. 60° E.; asc. 5 ft. over
SE. slope.

35.15 A point established and recorded by V. W. Hosford,
Registered Land Surveyor No. 253, in 1950, monumented
with an iron pipe, 1 in. diam., firmly set, projecting
5 ins. above ground, with steel plate, 2 ins. square,
welded on top, mkd.