

Dependent Resurvey of a Portion of the East Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

CHAINS	CC S 30 S 31 1950
	<p>from which bearing trees mkd. by Hosford</p> <p>A hemlock, 14 ins. diam., bears N. $43\frac{1}{2}^\circ$ E., 30 lks. dist., with scribe marks 25 R1W S30 CC PS 253 BT visible on open blaze.</p> <p>A cedar, 26 ins. diam., bears S. $36\frac{1}{2}^\circ$ E., $49\frac{1}{2}$ lks. dist., with scribe marks 25S R1W S31 CC PS 253 BT visible on open blaze.</p>
35.23	<p>From this point, the original closing cor. of secs. 30 and 31, T. 25 S., R. 1 W., bears East, 0.665 chs. dist., determined at record bearing and distance from the remains of the original bearing trees:</p> <p>A sawed cedar stump, 18 ins. diam., bears N. $62\frac{1}{2}^\circ$ E., 45 lks. dist., with scribe marks T25S R1W S30 BT visible on open blaze.</p> <p>A fir snag, 22 ins. diam., bears S. 51° E., 40 lks. dist., with scribe marks T25S R1W S31 BT visible on open blaze.</p>
	<p>Ascend 10 ft. over SE. slope, through logged area.</p>
37.30	<p>Top of ascent, slopes E.; desc. 15 ft. over broken NE. slope.</p>
40.69	<p>The $\frac{1}{2}$ sec. cor. of sec. 25 only, reestablished at proportionate distance and recorded by V. W. Hosford, Registered Land Surveyor No. 253, in 1950, and is accepted as the best available evidence of the position of the original corner, monumented with an iron pipe, 1 in. diam., firmly set, projecting 10 ins. above ground, with a steel plate, 2 ins. square, welded on top, mkd.</p>
	<p>$\frac{1}{2}$ S 25 1950</p>
	<p>from which bearing trees mkd. by Hosford</p> <p>A fir, 24 ins. diam., bears S. $11\frac{1}{2}^\circ$ W., 88 lks. dist., with healed blaze.</p> <p>A fir, 22 ins. diam., bears N. $55\frac{1}{2}^\circ$ W., 57 lks. dist., with healed blaze.</p>
	<p>N. $0^\circ 12'$ W., beginning new measurement.</p>
	<p>Descend 160 ft. over broken NE. slope.</p>
36.70	<p>Ridge, bears E. and W.; desc. 100 ft. over N. slope.</p>
40.69	<p>The cor. of secs. 24 and 25 only, reestablished at proportionate distance and recorded by V. W. Hosford, Registered Land Surveyor No. 253, in 1950, and perpetuated by Francis L. Ingram, County Surveyor, in 1976, and is accepted as the best available evidence of the position of the original corner, monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p>