

352

Dependent Resurvey of a Portion of the East Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

T 25 S		
R S 24		S 30 R
2 S 25		1
W		1976 W

from which the remains of bearing trees mkd. by Hosford

A sawed fir stump, 32 ins. diam., bears S. $78\frac{1}{2}^\circ$ W.,
54 $\frac{1}{2}$ lks. dist., with scribe marks T25S R2W S25
PS 253 BT visible on open blaze.

A sawed fir stump, 30 ins. diam., bears N. 39° W.,
25 lks. dist., with fragmentary scribe marks
visible on open blaze.

and a bearing tree mkd. by Ingram

A hemlock, 12 ins. diam., bears S. 50° W., 184 $\frac{1}{2}$
lks. dist., with fragmentary scribe marks
visible on open blaze.

No suitable tree available in sec. 24.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, maple, oak, madrone, alder,
and chinquapin; undergrowth, salal, rhododendron, vine
maple, Oregon grape, poison oak, and fern.

N. 0° 12' W., on the E. bdy. of sec. 24.

Descend 160 ft. over N. slope, through open logged area.

3.20 Creek, 2 lks. wide, course N. 75° E.; asc. 25 ft. over
SE. slope.

32.70 Ridge, bears N. 45° E. and S. 45° W.; desc. 5 ft. over
N. slope.

33.57 The closing cor. of secs. 19 and 30, T. 25 S., R. 1 W.,
reestablished at proportionate distance and recorded by
V. W. Hosford, Registered Land Surveyor No. 253, in 1950,
and is accepted as the best available evidence of the
position of the original corner, monumented with an iron
pipe, 24 ins. long, $\frac{3}{4}$ in. diam., firmly set, the top 2
ins. below the surface of the ground, from which the
remains of bearing trees mkd. by Hosford:

A root crown, bears N. $53\frac{3}{4}^\circ$ E., 25 lks. dist., with
a down fir alongside, 24 ins. diam., with scribe
marks 25S R1W S19 CC PS BT visible on open blaze.

A sawed hemlock stump, 23 ins. diam., bears
S. $37\frac{1}{2}^\circ$ E., 17 $\frac{1}{2}$ lks. dist., with scribe marks
25 30 CC visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 25 S		T 25 S
R 2 W		S 19
S 24		S 30 CC
		R 1 W
		1978