

Dependent Resurvey of a Portion of the East Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which new bearing trees</p> <p>A fir, 38 ins. diam., bears N. $43\frac{1}{2}^{\circ}$ E., 55 lks. dist., mkd. T25S R1W S19 CC BT.</p> <p>A fir, 4 ins. diam., bears S. $70\frac{1}{2}^{\circ}$ E., 83$\frac{1}{2}$ lks. dist., mkd. X BT.</p> <p>Reset iron pipe alongside iron post.</p> <p>Descend 160 ft. over broken N. slope.</p>
40.69	<p>The $\frac{1}{4}$ sec. cor. of sec. 24 only, reestablished at proportionate distance and recorded by V. W. Hosford, Registered Land Surveyor No. 253, in 1950, and is accepted as the best available evidence of the position of the original corner, monumented with an iron pipe, 1 in. diam., firmly set, projecting 10 ins. above ground, with a steel plate, 2 ins. square, welded on top, from which the remains of bearing trees mkd. by Hosford:</p> <p>A sawed fir stump, 32 ins. diam., bears S. 57° W., 25$\frac{1}{2}$ lks. dist., no marks visible on bark blaze.</p> <p>A sawed fir stump, 28 ins. diam., bears N. 27° W., 30 lks. dist., with scribe marks BT visible on open blaze.</p> <p>No new suitable trees available.</p> <hr/> <p>N. 0° 12' W., beginning new measurement.</p> <p>Descend 300 ft. over NW. slope.</p>
13.30	<p>Point for the S $\frac{1}{16}$ sec. cor. of sec. 19 only, T. 25 S., R. 1 W.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> S $\frac{1}{16}$ S 19 1978</p> <p>from which</p> <p>A hemlock, 8 ins. diam., bears N. $36\frac{1}{2}^{\circ}$ E., 87 lks. dist., mkd. S $\frac{1}{16}$ S19 BT.</p> <p>A cedar, 4 ins. diam., bears S. 29° E., 10 lks. dist., mkd. S $\frac{1}{16}$ S19 BT.</p> <p>Descend 200 ft. over broken NW. slope.</p>
25.00	<p>Creek, 3 lks. wide, course N.; desc. 235 ft. along creek bottom.</p>
33.72	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 19 only, T. 25 S., R. 1 W., determined at midpoint latitudinally on the W. bdy. of the sec.</p> <p>Seat a brass tablet, 3$\frac{1}{2}$ ins. diam., 3$\frac{1}{2}$ ins. stem, in drill hole, in solid rock creek bottom, with top mkd.</p> <p style="text-align: center;"> T 25 S $\frac{1}{4}$ S 19 R 1 W 1978</p>