

Dependent Resurvey of a Portion of the East Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

CHAINS	
	<p>N. 0° 12' W., on the E. bdy. of sec. 13.</p> <p>Descend 265 ft. over broken NE. slope, through heavy timber and dense undergrowth.</p>
20.345	<p>Point for the S 1/16 sec. cor. of sec. 13 only.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S 1/16 S 13 1978</p>
	<p>from which</p>
	<p>A fir, 5 ins. diam., bears S. 65½° W., 33½ lks. dist., mkd. S 1/16 S13 BT.</p>
	<p>A fir, 4 ins. diam., bears N. 30½° W., 8½ lks. dist., mkd. X BT.</p>
	<p>Descend 220 ft. over broken NE. slope.</p>
33.87	<p>Point for the closing cor. of secs. 18 and 19, T. 25 S., R. 1 W., at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 25 S T 25 S S 13 S 18 R 2 W S 19 CC R 1 W 1978</p>
	<p>from which</p>
	<p>A fir, 6 ins. diam., bears N. 71½° E., 10 lks. dist., mkd. T25S R1W S18 CC BT.</p>
	<p>A fir, 6 ins. diam., bears S. 39¼° E., 20½ lks. dist., mkd. T25S R1W S19 CC BT.</p>
	<p>Descend 55 ft. over NE. slope.</p>
35.65	<p>Mace Creek, 10 lks. wide, course N. 65° W.; asc. 100 ft. over SW. slope.</p>
40.69	<p>Point for the ¼ sec. cor. of sec. 13 only, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 25 S ¼ S 13 R 2 W 1978</p>
	<p>from which a bearing tree of which I have no record</p>
	<p>A fir, 10 ins. diam., bears S. 18° E., 30½ lks. dist., with scribe marks ¼ S18 BT visible on open blaze.</p>