

356

Dependent Resurvey of a Portion of the East Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

CHAINS											
	<p>and new bearing trees</p> <p>A fir, 3 ins. diam., bears S. $60\frac{1}{2}^{\circ}$ W., 42 lks. dist., mkd. X BT.</p> <p>A fir, 16 ins. diam., bears N. $12\frac{1}{2}^{\circ}$ W., $86\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S13 BT.</p> <p>Ascend 80 ft. over SW. slope.</p>										
42.25	Spur, slopes W.; desc. 335 ft. over broken NW. slope.										
66.35	Paved road, 50 lks. wide, bears N. 70° W. and S. 80° E.										
67.05	East Fork of Rock Creek, 30 lks. wide, course N. 70° W.; asc. 105 ft. over broken S. slope.										
74.50	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 18 only, T. 25 S., R. 1 W., determined at midpoint latitudinally on the W. bdy. of the sec.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td> </td><td>T 25 S</td></tr> <tr><td> </td><td>$\frac{1}{4}$</td></tr> <tr><td> </td><td>S 18</td></tr> <tr><td> </td><td>R 1 W</td></tr> <tr><td> </td><td>1978</td></tr> </table> </div> <p>from which</p> <p>A fir, 4 ins. diam., bears N. $15\frac{1}{2}^{\circ}$ E., $27\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S18 BT.</p> <p>A fir, 7 ins. diam., bears S. 39° E., $49\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S18 BT.</p> <p>Ascend 480 ft. over steep S. slope.</p>		T 25 S		$\frac{1}{4}$		S 18		R 1 W		1978
	T 25 S										
	$\frac{1}{4}$										
	S 18										
	R 1 W										
	1978										
81.27	<p>Intersect a point established by V. W. Hosford, Registered Land Surveyor No. 253, in 1950, monumented with an iron pipe, $1\frac{1}{2}$ ins. diam., firmly set, projecting 10 ins. above ground, with a steel plate, 2 ins. square, welded on top, mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td> </td><td>S 12</td></tr> <tr><td> </td><td>S 13</td></tr> <tr><td> </td><td>1950</td></tr> </table> </div> <p>from which the remains of bearing trees mkd. by Hosford</p> <p>A fir snag, 26 ins. diam., bears S. 52° W., 39 lks. dist., with fragmentary scribe marks visible on open blaze.</p> <p>A sawed cedar stump, 36 ins. diam., bears N. 73° W., $55\frac{1}{2}$ lks. dist., with scribe marks T25S R2W S12 PS 253 BT visible on open blaze.</p>		S 12		S 13		1950				
	S 12										
	S 13										
	1950										
81.38	<p>Point for the cor. of secs. 12 and 13 only, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										