

Dependent Resurvey of a Portion of the East Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

T 25 S	T 25 S
S 12	S 18
S 13	R 1 W
R 2 W	
	1978

from which

A boulder, in place, 5 x 4 x 3 ft. above ground,
bears S. $50\frac{1}{2}^{\circ}$ W., 23 lks. dist., mkd. X BO
on top.

No suitable trees available within limits.

Land, mountainous.

Soil, sandy clay.

Timber, fir, hemlock, cedar, maple, oak, madrone, alder,
and chinquapin; undergrowth, salal, poison oak, vine
maple, rhododendron, Oregon grape, and fern.

N. $0^{\circ} 12'$ W., on the E. bdy. of sec. 12.

Ascend 440 ft. over SW. slope, through heavy timber and
dense undergrowth.

13.435 Point for the N 1/16 sec. cor. of sec. 18 only, T. 25 S.,
R. 1 W.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

N 1/16	
S 18	
	1978

from which

A cedar, 5 ins. diam., bears N. $78\frac{1}{2}^{\circ}$ E., $53\frac{1}{2}$ lks.
dist., mkd. N 1/16 S18 BT.

A cedar, 8 ins. diam., bears S. $28\frac{3}{4}^{\circ}$ E., 103 lks.
dist., mkd. N 1/16 S18 BT.

Ascend 335 ft. over SW. slope.

33.45 Gravelled road, 20 lks. wide, bears N. 80° W. and
S. 80° E.

33.75 The closing cor. of secs. 7 and 18, monumented with an
iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 8 ins.
above ground, with brass cap mkd.

T 25 S	T 25 S
S 12	S 7
R 2 W	S 18
	R 1 W
	CC
	CS 1978
	1957

from which the remains of a bearing tree mkd. by Roseberry

A root hole, bears N. 81° E., 24 lks. dist., with
a down fir alongside, 15 ins. diam., with frag-
mentary scribe marks visible on open blaze.

and the remains of a bearing tree mkd. by V. W. Hosford,
Registered Land Surveyor No. 253, in 1950