

356

Dependent Resurvey of a Portion of the East Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

A root hole, bears N. 78° E., 17 lks. dist., with a down fir alongside, 15 ins. diam., with healed blaze.

and the remains of a bearing tree mkd. by Gary Langlitz, Deputy County Surveyor, in 1978

A sawed fir stump, 54 ins. diam., bears N. 58½° W., 91½ lks. dist., with railroad spike driven in top.

add reference monuments

An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 61° E., 33 lks. dist., with brass cap mkd. T25S R1W S7 CC RM 1978 and an arrow pointing to the corner.

An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 70° E., 29 lks. dist., with brass cap mkd. T25S R1W S18 CC RM 1978 and an arrow pointing to the corner.

From this point, a point established by V. W. Hosford, Registered Land Surveyor No. 253, in 1950, bears S. 16° E., 0.11 chs. dist., monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 6 ins. above ground, with a steel plate, 2 ins. square, welded on top.

Ascend 135 ft. over SW. slope.

40.69

The ¼ sec. cor. of sec. 12 only, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

¼ S 12 |
1951

from which the remains of bearing trees mkd. by Tallett

A sawed fir stump, 14 ins. diam., bears S. 7° W., 20 lks. dist., with axe marks visible on open blaze.

A cedar, 9 ins. diam., bears N. 20° W., 49 lks. dist., with healed blaze.

and bearing trees mkd. by V. W. Hosford, Registered Land Surveyor No. 253, in 1950

A fir, 18 ins. diam., bears S. 11½° W., 27½ lks. dist., with fragmentary scribe marks visible on open blaze.

A fir, 26 ins. diam., bears N. 50½° W., 23½ lks. dist., with healed blaze.

Land, mountainous.

Soil, sandy clay.

Timber, fir, hemlock, cedar, maple, oak, madrone, alder, and chinquapin; undergrowth, salal, poison oak, vine maple, rhododendron, Oregon grape, and fern.