

T. 25 S., R. 1 W., Willamette Meridian, Oregon

CHAINS

Dependent Resurvey of a Portion of the North Boundary,
T. 25 S., R. 1 W., Willamette Meridian, Oregon

(Restoring the survey by Carl S. Nicklin,
U. S. Deputy Surveyor, in 1896)

From the cor. of secs. 3, 4, 33, and 34, on the N. bdy.
of the Tp., perpetuated and recorded by Milo E. Godfrey,
Deputy County Surveyor, in 1966, monumented with an iron
post, 1½ ins. diam., firmly set, projecting 8 ins. above
ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 24 S
S 33 | S 34 R 1 W
S 4 | S 3
T 25 S
1966

from which the original bearing trees

A fir, 54 ins. diam., bears N. 18° E., 67 lks.
dist., with fragmentary scribe marks visible
on open blaze.

A fir, 24 ins. diam., bears S. 29° E., 44 lks.
dist., with healed blaze. (Record, 42 lks.)

A fir, 60 ins. diam., bears S. 35° W., 37 lks.
dist., with healed blaze. (Record, 43 lks.)

A fir, 55 ins. diam., bears N. 24° W., 64 lks.
dist., with healed blaze.

S. 89° 58' W., bet. secs. 4 and 33, marking and blazing
the true line.

Ascend 285 ft. over broken NE. slope, through heavy
timber and dense undergrowth.

9.90 Spur, slopes N.; desc. 50 ft. over NW. slope.

17.20 Ravine, drains N., also enter logged area, edge bears
N. and S.; asc. 60 ft. over NE. slope.

19.94 The E 1/16 sec. cor. of secs. 4 and 33, established and
recorded by Thomas E. Shrum, Jr., Registered Engineer
No. 4287, in 1964, and perpetuated by Francis L. Ingram,
County Surveyor, in 1976, and is accepted as the corner,
monumented with an iron post, ¾ in. diam., firmly set,
projecting 10 ins. above ground, with aluminum cap mkd.

T 24 S R 1 W
33
4
E 1/16 RE 4287
1964

from which the remains of a bearing tree mkd. by Shrum

A cedar stump, 8 ins. diam., bears S. 70° W., 14½
lks. dist., with scribe marks BT visible on
open blaze.

and the remains of a bearing tree mkd. by Ingram