

360

Dependent Resurvey of a Portion of the North Boundary,  
T. 25 S., R. 1 W., Willamette Meridian, Oregon

CHAINS

A hemlock stump, 48 ins. diam., bears S.  $41\frac{1}{2}^{\circ}$  W.,  
48 $\frac{1}{2}$  lks. dist., with scribe marks 1/16 S4 CS BT  
visible on open blaze, and a star drill, 12 ins.  
long,  $\frac{3}{8}$  in. diam., driven flush in the top, in  
center of stump.

No suitable trees available within limits.

S.  $89^{\circ} 51'$  W., beginning new measurement.

Ascend 75 ft. over NE. slope, across logged area.

5.40 Spur, slopes S.  $50^{\circ}$  E.; asc. 75 ft. over NE. slope.

13.10 Spur, slopes S.; desc. 150 ft. over SW. slope.

19.89 The  $\frac{1}{4}$  sec. cor. of secs. 4 and 33, perpetuated and re-  
corded by Milo E. Godfrey, Deputy County Surveyor, in  
1962, and further perpetuated by Vernon R. Tracy, Deputy  
County Surveyor, in 1966, monumented with an iron post,  
 $1\frac{1}{2}$  ins. diam., firmly set, projecting 4 ins. above ground,  
with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 24 S

$\frac{1}{4}$   $\frac{S 33}{S 4}$  R 1 W

T 25 S

1966

from which the remains of an original bearing tree

A hemlock snag, 40 ins. diam., bears N.  $55^{\circ}$  W.,  
17 lks. dist., with scribe marks  $\frac{1}{4}$  S33 BT  
visible on open blaze.

and the remains of a bearing tree mkd. by Godfrey

A root hole, bears N.  $12^{\circ}$  W., 58 $\frac{1}{2}$  lks. dist., with  
a down hemlock alongside, 8 ins. diam., with  
scribe marks  $\frac{1}{4}$  S33 CS BT visible on open blaze.

and the remains of bearing trees mkd. by Tracy

A sawed hemlock stump, 11 ins. diam., bears  
N.  $83^{\circ}$  E., 91 lks. dist., with a down log  
alongside, with fragmentary scribe marks  
visible on open blaze.

A root hole, bears S.  $29^{\circ}$  W., 60 $\frac{1}{2}$  lks. dist., with  
a down hemlock alongside, 6 ins. diam., with  
fragmentary scribe marks visible on open blaze.

No suitable trees available within limits.

S.  $88^{\circ} 56'$  W., beginning new measurement.

Descend 35 ft. over W. slope.

3.00 Creek, 3 lks. wide, course S.; asc. 55 ft. over broken  
SE. slope.

20.235 The W 1/16 sec. cor. of secs. 4 and 33, established and  
recorded by Thomas E. Shrum, Jr., Registered Engineer,  
No. 4287, in 1964, and is accepted as the corner, monu-  
ment with an iron post,  $\frac{1}{4}$  in. diam., firmly set,  
projecting 8 ins. above ground, with aluminum cap mkd.