

Dependent Resurvey of a Portion of the North Boundary,
T. 25 S., R. 1 W., Willamette Meridian, Oregon

CHAINS

T 24 S R 1 W

33

4

W 1/16 RE 4287

1964

from which the remains of bearing trees mkd. by Shrum

A sawed hemlock stump, 22 ins. diam., bears
N. 24° W., 5½ lks. dist., with fragmentary
scribe marks visible on open blaze.

A hemlock, 14 ins. diam., bears S. 21½° W., 47½
lks. dist., with healed blaze.

No other suitable trees available within limits.

S. 88° 56' W., beginning new measurement.

Ascend 195 ft. over SE. slope.

2.90 Dirt road, 30 lks. wide, bears N. 10° W. and S. 10° E.,
also enter timber, edge bears N. and E.

8.00 Ridge, bears N. and S.; desc. 240 ft. over NW. slope.

18.15 Gravelled road, 40 lks. wide, bears N. 20° E. and
S. 70° W.

20.235 The cor. of secs. 4, 5, 33, and 34, perpetuated and re-
corded by Milo E. Godfrey, Deputy County Surveyor, in
1962, monumented with an iron post, 1½ ins. diam., firmly
set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 24 S R 1 W

S 32 | S 33

S 5 | S 4

T 25 S

1962

from which the remains of the original bearing trees

A root hole, bears N. 60° E., 8 lks. dist., with
a down fir alongside, 11 ins. diam., with healed
blaze.

A fir, 35 ins. diam., bears S. 10° E., 51 lks.
dist., with healed blaze.

A root hole, bears S. 51½° W., 6 lks. dist., with
a down fir alongside, 12 ins. diam., with
fragmentary scribe marks visible on open blaze.

A root hole, bears N. 44° W., 28 lks. dist., with
a down fir alongside, 14 ins. diam., with healed
blaze.

and bearing trees mkd. by Godfrey

A hemlock, 9 ins. diam., bears N. 45° E., 35 lks.
dist., with healed blaze.

A fir, 16 ins. diam., bears S. 24° W., 34½ lks.
dist., with healed blaze.

A fir, 11 ins. diam., bears N. 20° W., 22½ lks.
dist., with healed blaze.