

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 1 W., Willamette Meridian, Oregon

CHAINS					
	<p>and new bearing trees</p> <p>A hemlock, 10 ins. diam., bears S. 23° E., 65 lks. dist., mkd. N 1/16 S3 BT.</p> <p>A hemlock, 8 ins. diam., bears S. 24° W., 37 lks. dist., mkd. N 1/16 S4 BT.</p> <hr/> <p>N. 4° 34' E., beginning new measurement.</p> <p>Ascend 300 ft. over SE. slope.</p>				
12.80	Spur, slopes S. 70° E.; desc. 175 ft. over NE. slope.				
22.53	<p>The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, maple, oak, madrone, alder, chinquapin, and live oak; undergrowth, salal, Oregon grape, rhododendron, vine maple, poison oak, and fern.</p>				
	<p>From the cor. of secs. 28, 29, 32, and 33, perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1961, monumented with an iron post, 1½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>COUNTY SURVEYORS OFFICE</p> <p>T 25 S R 1 W</p> <table style="margin: auto;"> <tr> <td>S 29</td> <td>S 28</td> </tr> <tr> <td>S 32</td> <td>S 33</td> </tr> </table> <p>1961</p> </div> <div style="text-align: right; margin-top: 10px;"> <p><i>FD. OK</i> <i>3/17/92</i> <i>BLM</i> <i>CS. 62/140</i></p> </div> <p>from which the remains of an original bearing tree</p> <p>A fir snag, 30 ins. diam., bears S. 40° E., 23 lks. dist., with fragmentary scribe marks visible on open blaze.</p> <p>and bearing trees mkd. by Godfrey</p> <p>A fir, 15 ins. diam., bears N. 45° E., 39 lks. dist., with healed blaze.</p> <p>A fir, 12 ins. diam., bears S. 39° E., 11½ lks. dist., with healed blaze.</p> <p>A fir, 8 ins. diam., bears S. 31° W., 20½ lks. dist., with healed blaze.</p> <p>A fir, 13 ins. diam., bears N. 30° W., 7½ lks. dist., with healed blaze.</p> <p>N. 0° 43' W., bet. secs. 28 and 29.</p> <p>Ascend 175 ft. over broken SE. slope, through heavy timber and dense undergrowth.</p>	S 29	S 28	S 32	S 33
S 29	S 28				
S 32	S 33				
15.75	Spur, slopes N. 60° E.; desc. 315 ft. over broken NW. slope.				
18.90	Dirt road, 10 lks. wide, bears N. 70° E. and S. 70° W.				
36.05	Ravine, drains N. 75° W.; asc. 15 ft. over SW. slope.				