

354

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 1 W., Willamette Meridian, Oregon

CHAINS	
37.60	Top of ascent, slopes W.; desc. 10 ft. over NW. slope.
38.70	Ravine, drains S. 45° W.; asc. 65 ft. over SW. slope.
40.50	Point for the $\frac{1}{2}$ sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 S R 1 W $\frac{1}{2}$ S 29 S 28 1978 </div> from which A fir, 7 ins. diam., bears S. 20° E., 65 lks. dist., mkd. $\frac{1}{4}$ S28 BT. A fir, 9 ins. diam., bears N. 72 $\frac{3}{4}$ ° W., 26 lks. dist., mkd. $\frac{1}{4}$ S29 BT. Ascend 110 ft. over broken SW. slope.
50.00	Spur, slopes N. 60° W.; desc. 665 ft. over steep N. slope.
52.45	Dirt road, 25 lks. wide, bears N. 80° W. and S. 80° E.
56.00	Same road, 25 lks. wide, bears N. 75° E. and S. 80° W.
66.60	Creek, 2 lks. wide, course N. 30° W.; asc. 195 ft. over SW. slope.
81.00	The cor. of secs. 20, 21, 28, and 29, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1967, and redescribed by James E. Jelley, in 1969, monumented with an iron post, 1 $\frac{1}{2}$ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. <div style="text-align: center;"> COUNTY SURVEYORS OFFICE T 25 S S 20 S 21 S 29 S 28 R 1 W 1967 </div> from which the remains of the original bearing trees A fir snag, 48 ins. diam., bears N. 39 $\frac{1}{2}$ ° E., 59 lks. dist., with fragmentary scribe marks visible on open blaze. (Record, N. 36 $\frac{1}{2}$ ° E., 54 lks.) A madrone, 18 ins. diam., bears N. 70 $\frac{1}{2}$ ° W., 25 lks. dist., with healed blaze. and bearing trees mkd. by Tracy A madrone, 11 ins. diam., bears North, 52 lks. dist., with scribe marks T25S R1W S21 CS visible on open blaze. A fir, 12 ins. diam., bears S. 60 $\frac{1}{2}$ ° E., 39 lks. dist., with fragmentary scribe marks visible on open blaze.