

16345

357

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 25 S., R. 1 W., Willamette Meridian, Oregon

CHAINS

A cedar, 20 ins. diam., bears S. 22° W., 85½ lks. dist., with fragmentary scribe marks visible on open blaze.

A hemlock, 18 ins. diam., bears N. 80° W., 36½ lks. dist., with fragmentary scribe marks visible on open blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, maple, oak, madrone, alder, and chinquapin; undergrowth, salal, rhododendron, Oregon grape, vine maple, and fern.

N. 3° 10' E., bet. secs. 4 and 5.

Descend 95 ft. over broken N. slope, across logged area.

8.50 Creek, 2 lks. wide, course N. 45° W.; asc. 150 ft. over SW. slope.

20.685 Point for the S 1/16 sec. cor. of secs. 4 and 5.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16  
S 5 | S 4  
1978

from which

A fir, 18 ins. diam., bears N. 53½° E., 27 lks. dist., mkd. S 1/16 S4 BT.

A fir, 13 ins. diam., bears N. 51° W., 31½ lks. dist., mkd. S 1/16 S5 BT.

Leave logged area, edge bears E. and W.; asc. 350 ft. over broken SW. slope, through heavy timber and dense undergrowth.

35.95 Paved road, 30 lks. wide, bears N. 45° W. and S. 45° E.

40.20 Spur, slopes S. 45° W.; desc. 40 ft. over NW. slope.

41.37 Point for the ¼ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 S R 1 W  
¼  
S 5 | S 4  
1978

from which

A fir, 30 ins. diam., bears S. 64½° E., 14½ lks. dist., mkd. ¼ S4 BT.

A fir, 15 ins. diam., bears N. 60° W., 22½ lks. dist., mkd. ¼ S5 BT.

Descend 155 ft. over broken NW. slope.