

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 1 W., Willamette Meridian, Oregon

CHAINS	
	T 25 S R 1 W $\frac{1}{2}$ S 31 S 32 1980
	from which new bearing trees A fir, 15 ins. diam., bears S. 64° E., 39½ lks. dist., mkd. ¼ S32 BT. A fir, 8 ins. diam., bears S. 83½° W., 16½ lks. dist., mkd. ¼ S31 BT. Deposit corner stone alongside iron post. N. 0° 07' E., bet. secs. 31 and 32. Ascend 75 ft. over SW. slope, through heavy timber and dense undergrowth.
9.90	Creek, 3 lks. wide, course S. 35° W.; asc. 180 ft. over SE. slope.
15.90	Ravine, drains S. 20° E.; asc. 85 ft. over SW. slope.
18.90	Same ravine, drains S. 10° W.; asc. 175 ft. over SE. slope.
22.90	Head of same ravine, drains S. 20° E.; asc. 545 ft. over SE. slope.
39.75	Ridge, bears S. 80° E. and S. 80° W., also dirt road, 15 lks. wide, bears same as ridge; desc. 1 ft. over N. slope.
39.92	Point for the cor. of secs. 29, 30, 31, and 32, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 S R 1 W S 30 S 29 S 31 S 32 1978
	from which A fir, 9 ins. diam., bears N. 67½° E., 37½ lks. dist., mkd. T25S R1W S29 BT. A fir, 15 ins. diam., bears S. 15½° E., 77 lks. dist., mkd. T25S R1W S32 BT. A fir, 11 ins. diam., bears S. 48° W., 101 lks. dist., mkd. T25S R1W S31 BT. A fir, 10 ins. diam., bears N. 15° W., 20 lks. dist., mkd. T25S R1W S30 BT. Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, maple, oak, madrone, alder, and chinquapin; undergrowth, salal, Oregon grape, vine maple, rhododendron, poison oak, and fern.

*FD. OK 3/17/92
B.L.M.
C.S. 63/140*