

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 1 W., Willamette Meridian, Oregon

CHAINS
39.22

The $\frac{1}{4}$ sec. cor. of secs. 30 and 31, perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1961, mkd. with an X in NW. face of rock outcropping, from which the remains of the original bearing trees:

A root hole, bears N. 86° W., 79 lks. dist.

A root hole, bears S. 14° W., 31 lks. dist.

and bearing trees mkd. by Godfrey

A fir, 16 ins. diam., bears N. 62° E., 105 lks. dist., with healed blaze.

A fir, 10 ins. diam., bears S. 55° E., 110 lks. dist., with healed blaze.

At the corner point

Set a brass tablet, $3\frac{1}{2}$ ins. diam., $3\frac{1}{2}$ ins. stem, in drill hole, in rock outcropping, with top mkd.

T 25 S R 1 W
 $\frac{1}{4}$ S 30
S 31
1978

*FD: OK
3/17/92
B.L.M.
C.S. 63/140*

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, maple, oak, alder, madrone, and chinquapin; undergrowth, salal, rhododendron, vine maple, poison oak, Oregon grape, and fern.

From the cor. of secs. 29, 30, 31, and 32.

N. $0^\circ 52'$ E., bet. secs. 29 and 30.

Descend 500 ft. over NE. slope, through heavy timber and dense undergrowth.

14.50 Ravine, drains N. 30° E.; desc. 30 ft. over broken NE. slope.

37.50 Ravine, drains N. 45° E.; asc. 100 ft. over SE. slope.

39.93 Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 S R 1 W
 $\frac{1}{4}$
S 30 | S 29
1978

from which

A fir, 12 ins. diam., bears N. $56\frac{1}{2}^\circ$ E., 50 lks. dist., mkd. $\frac{1}{4}$ S29 BT.

A fir, 10 ins. diam., bears N. 47° W., 47 lks. dist., mkd. $\frac{1}{4}$ S30 BT.

Ascend 135 ft. over SE. slope.

46.60 Spur, slopes N. 50° E.; desc. 170 ft. over NE. slope.