

372

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 1 W., Willamette Meridian, Oregon

CHAINS 50.50	Ravine, drains N. 40° E.; asc. 120 ft. over SE. slope.
59.88	Point for the N 1/16 sec. cor. of secs. 29 and 30. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	N 1/16 S 30 S 29 1978
	from which A fir, 17 ins. diam., bears S. 62¾° E., 10½ lks. dist., mkd. N 1/16 S29 BT. A fir, 16 ins. diam., bears N. 56° W., 13½ lks. dist., mkd. N 1/16 S30 BT. Ascend 50 ft. over SE. slope.
64.00	Spur, slopes N. 45° E.; desc. 700 ft. over NW. slope, changing to NE. slope.
79.84	The cor. of secs. 19, 20, 29, and 30, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1967, and redescribed by James E. Jelley, in 1969, monumented with an iron post, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.
	T 25 S S 19 S 20 S 30 S 29 R 1 W 1967
	from which the remains of an original bearing tree A decayed fir stump, 9 ins. diam., bears N. 77° W., 15 lks. dist., with axe marks visible on bark. and bearing trees mkd. by V. W. Hosford, Registered Land Surveyor No. 253, in 1950 A fir, 20 ins. diam., bears N. 66½° E., 19 lks. dist., with healed blaze. A fir, 22 ins. diam., bears S. 71¾° E., 14 lks. dist., with fragmentary scribe marks visible on open blaze. A fir, 30 ins. diam., bears S. 42¾° W., 50½ lks. dist., with healed blaze. (Record, S. 45¾° W., 47 lks.) A fir, 25 ins. diam., bears N. 48½° W., 83 lks. dist., with healed blaze. (Record, N. 45° W.)
	Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, maple, oak, madrone, alder, and chinquapin; undergrowth, salal, rhododendron, Oregon grape, vine maple, poison oak, and fern.
	N. 89° 29' W., bet. secs. 19 and 30.
	Ascend 10 ft. over NE. slope, through heavy timber and dense undergrowth.