

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 25 S., R. 1 W., Willamette Meridian, Oregon

CHAINS 1.05	Spur, slopes N. 50° W.; desc. 295 ft. over NW. slope.
7.60	Ravine, drains N.; asc. 225 ft. over NE. slope.
20.30	Point for the E 1/16 sec. cor. of secs. 19 and 30. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. $\begin{array}{c} \text{E } 1/16 \quad \frac{\text{S } 19}{\text{S } 30} \\ 1978 \end{array}$ from which A fir, 15 ins. diam., bears N. 51° E., 10½ lks. dist., mkd. E 1/16 S19 BT. A fir, 15 ins. diam., bears S. 20¼° E., 9½ lks. dist., mkd. E 1/16 S30 BT. Corner is located on spur, slopes N. 10° W.; desc. 780 ft. over NW. slope.
36.40	Cougar Creek, 6 lks. wide, course N.; asc. 260 ft. over NE. slope.
40.60	Point for the ¼ sec. cor. of secs. 19 and 30, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. $\begin{array}{c} \text{T } 25 \text{ S } \text{R } 1 \text{ W} \\ \frac{1}{4} \quad \frac{\text{S } 19}{\text{S } 30} \\ 1978 \end{array}$ from which A hemlock, 9 ins. diam., bears N. 54¾° E., 25½ lks. dist., mkd. ¼ S19 BT. A fir, 9 ins. diam., bears S. 64° W., 54 lks. dist., mkd. ¼ S30 BT. Ascend 765 ft. over NE. slope.
59.80	Spur, slopes N. 20° E.; desc. 85 ft. over NW. slope.
65.30	Creek, 1 lk. wide, course N. 20° E.; asc. 185 ft. over NE. slope.
73.35	Spur, slopes N. 20° E.; desc. 720 ft. over NW. slope.
98.35	Creek, 3 lks. wide, course N.; asc. 240 ft. over NE. slope.
104.55	Spur, slopes N. 10° E.; desc. 85 ft. over NW. slope.
109.35	Creek, 1 lk. wide, course N. 10° E.; asc. 355 ft. over NE. slope.
121.80	Point for the 120 1/16 sec. cor. of secs. 19 and 30. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. $\begin{array}{c} 1/16 \quad \frac{\text{S } 19}{\text{S } 30} \quad 120 \\ 1978 \end{array}$