

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 25 S., R. 1 W., Willamette Meridian, Oregon

CHAINS	
12.75	Ridge, bears N. 20° E. and S. 20° W.; desc. 380 ft. over SW. slope.
24.10	Creek, 1 lk. wide, course S. 30° W.; asc. 70 ft. over SE. slope.
31.90	Spur, slopes S. 30° W.; desc. 150 ft. over SW. slope.
39.90	Dirt road, 15 lks. wide, bears N. 15° W. and S. 15° E.
40.71	Point for the ¼ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 25 S R 1 W                    ¼ S 18                    S 19                    1978</p>
	from which
	A fir, 5 ins. diam., bears N. 50½° E., 15 lks. dist., mkd. ¼ S18 BT.
	A fir, 5 ins. diam., bears S. 32¼° E., 9½ lks. dist., mkd. ¼ S19 BT.
	Descend 130 ft. over SW. slope.
42.75	Ravine, drains S. 25° W.; asc. 110 ft. over SE. slope.
53.25	Spur, slopes S.; desc. 335 ft. over SW. slope.
61.40	Creek, 1 lk. wide, course S. 35° W.; asc. 40 ft. over SE. slope.
71.85	Spur, slopes S. 10° W.; desc. 355 ft. over SW. slope.
85.90	Gravelled road, 40 lks. wide, bears N. 50° W. and S. 50° E.
90.75	East Fork of Rock Creek, 20 lks. wide, course N. 50° W.; asc. 200 ft. over NE. slope.
99.50	Spur, slopes N. 5° E.; desc. 70 ft. over NW. slope.
104.00	Creek, 1 lk. wide, course N. 20° E.; asc. 400 ft. over NE. slope.
119.40	Ridge, bears N. 15° W. and S. 5° E.; desc. 530 ft. over SW. slope.
136.10	Creek, 3 lks. wide, course N. 65° W.; asc. 55 ft. over NE. slope.
138.16	Intersect the E. bdy. of sec. 13, T. 25 S., R. 2 W.
	The closing cor. of secs. 18 and 19, hereinbefore described.
	From this point, the ¼ sec. cor. of sec. 13 only, T. 25 S., R. 2 W., bears N. 0° 12' W., 6.82 chs. dist., hereinbefore described.