

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 1 W., Willamette Meridian, Oregon

| CHAINS | <p>Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, maple, oak, madrone, alder, and chinquapin; undergrowth, salal, vine maple, poison oak, rhododendron, Oregon grape, and fern.</p> |
|--------|---|
| | <p>Subdivision of Section 4, T. 25 S., R. 1 W., Willamette Meridian, Oregon</p> |
| | <p>From the $\frac{1}{2}$ sec. cor. of secs. 4 and 9. N. $3^{\circ} 01'$ E., on the N. and S. center line of sec. 4. Ascend 5 ft. over SE. slope, across logged area.</p> |
| 0.25 | <p>Spur, slopes E.; asc. 10 ft. over broken SE. slope.</p> |
| 20.49 | <p>Point for the center S $\frac{1}{16}$ sec. cor. of sec. 4. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C S $\frac{1}{16}$ S 4 C 1978</p> |
| | <p>from which</p> <p style="padding-left: 40px;">A chinquapin, 14 ins. diam., bears N. $73\frac{1}{2}^{\circ}$ E., 57$\frac{1}{2}$ lks. dist., mkd. CS $\frac{1}{16}$ S4 BT.</p> <p style="padding-left: 40px;">A yew, 13 ins. diam., bears S. $55\frac{1}{2}^{\circ}$ W., 57 lks. dist., mkd. CS $\frac{1}{16}$ S4 BT.</p> <p>Ascend 235 ft. over SE. slope.</p> |
| 25.50 | <p>Spur, slopes E.; desc. 355 ft. over broken NE. slope.</p> |
| 40.98 | <p>Point for the center $\frac{1}{2}$ sec. cor. of sec. 4, at inter- section with the E. and W. center line. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 S R 1 W C $\frac{1}{2}$ S 4 1978</p> |
| | <p>from which</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 84° E., 5$\frac{1}{2}$ lks. dist., mkd. C $\frac{1}{2}$ S4 BT.</p> <p style="padding-left: 40px;">A hemlock, 10 ins. diam., bears N. $72\frac{1}{2}^{\circ}$ W., 75$\frac{1}{2}$ lks. dist., mkd. C $\frac{1}{2}$ S4 BT.</p> <p>From this point, a corner established by Thomas E. Shrum, Jr., Registered Engineer No. 4287, in 1964, bears N. $71\frac{1}{2}^{\circ}$ W., 0.50 chs. dist., monumented with an iron post, $\frac{1}{2}$ in. diam., firmly set, projecting 10 ins. above ground, with aluminum cap mkd. T25S R1W S$\frac{1}{2}$ Sec 4 1964, from which the remains of a bearing tree mkd. by Shrum:</p> |