

16355

377

Subdivision of Section 4, T. 25 S., R. 1 W.,  
Willamette Meridian, Oregon

CHAINS	
	<p>A sawed fir stump, 20 ins. diam., bears N. <math>88\frac{1}{2}^{\circ}</math> W., <math>22\frac{1}{2}</math> lks. dist., with fragmentary scribe marks visible on open blaze.</p>
	<p>Descend 150 ft. over NE. slope.</p>
56.90	<p>Creek, 3 lks. wide, course S. <math>45^{\circ}</math> E.; asc. 160 ft. over broken S. slope.</p>
62.615	<p>Point for the center N 1/16 sec. cor. of sec. 4.</p>
	<p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">C N 1/16   S 4 C 1978</p>
	<p>from which</p>
	<p>An iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., set 24 ins. in the ground, for a reference monument, bears N. <math>42\frac{1}{2}^{\circ}</math> E., <math>27\frac{1}{2}</math> lks. dist., with brass cap mkd. CN 1/16 S4 RM 1978, and an arrow pointing to the corner.</p>
	<p>A hemlock, 6 ins. diam., bears S. <math>73\frac{1}{2}^{\circ}</math> W., 36 lks. dist., mkd. CN 1/16 S4 BT.</p>
	<p>From this point, a corner established by Thomas E. Shrum, Jr., Registered Engineer No. 4287, in 1964, bears N. <math>50\frac{1}{2}^{\circ}</math> W., 0.20 chs. dist., monumented with an iron post, <math>\frac{3}{4}</math> in. diam., firmly set, projecting 18 ins. above ground, with aluminum cap mkd. T25S R1W CN 1/16 Sec 4 RE 4287 1964, from which the remains of a bearing tree mkd. by Shrum:</p>
	<p>A hemlock stump, 18 ins. diam., bears N. <math>25^{\circ}</math> E., 18 lks. dist., with scribe marks CN 1/16 S4 BT visible on open blaze.</p>
	<p>Ascend 470 ft. over broken S. slope.</p>
68.50	<p>Dirt road, 25 lks. wide, bears N. <math>75^{\circ}</math> W. and S. <math>75^{\circ}</math> E.</p>
84.62	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.</p>
	<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 3 and 4.</p>
	<p>N. <math>88^{\circ} 31'</math> W., on the E. and W. center line of sec. 4.</p>
	<p>Descend 170 ft. over SW. slope, through heavy timber and dense undergrowth.</p>
14.10	<p>Gravelled road, 30 lks. wide, bears N. <math>10^{\circ}</math> E. and S. <math>45^{\circ}</math> E., also enter logged area, edge bears same as road.</p>
19.31	<p>Point for the center E 1/16 sec. cor. of sec. 4.</p>
	<p>Seat a brass tablet, <math>3\frac{1}{4}</math> ins. diam., <math>3\frac{1}{2}</math> ins. stem, in drill hole, in exposed bedrock, with top mkd.</p>
	<p style="text-align: center;">C E 1/16 C S 4 1978</p>