

376

Subdivision of Section 4, T. 25 S., R. 1 W.,
Willamette Meridian, Oregon

CHAINS	
	<p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 80¾° E., 41 lks. dist., with brass cap mkd. CE 1/16 S4 RM 1978 and an arrow pointing to the corner.</p> <p>A boulder, 5 x 4 x 4 ft. above ground, bears N. 21¾° W., 67 lks. dist., mkd. X BO.</p> <p>Set a 6 ft. steel fence post alongside reference monument.</p> <p>Descend 5 ft. over SW. slope.</p>
19.40	Creek, 6 lks. wide, course S. 45° E.; asc. 345 ft. over broken E. slope.
37.30	Top of ascent, slopes N.; desc. 10 ft. over NW. slope.
38.62	The center ¼ sec. cor. of sec. 4.
	Ascend 170 ft. over broken NE. slope.
58.65	Leave logged area, enter timber, edge bears N. and S.
58.86	Point for the center W 1/16 sec. cor. of sec. 4.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \text{W } 1/16 \\ \text{C} \quad \text{---} \quad \text{C} \\ \text{S } 4 \\ 1978 \end{array}$
	<p>from which</p> <p>A fir, 10 ins. diam., bears N. 11° E., 41 lks. dist., mkd. CW 1/16 S4 BT.</p> <p>A fir, 13 ins. diam., bears S. 16° E., 40 lks. dist., mkd. CW 1/16 S4 BT.</p> <p>Ascend 300 ft. over E. slope.</p>
66.60	Gravelled road, 30 lks. wide, bears N. and S.
70.35	Ridge, bears N. and S.; desc. 145 ft. over NW. slope.
79.10	The ¼ sec. cor. of secs. 4 and 5.
	<p>From the center E 1/16 sec. cor. of sec. 4.</p> <p>N. 3° 44' E., on the N. and S. center line of the NE¼ of sec. 4.</p> <p>Ascend 545 ft. over broken SW. slope, across logged area.</p>
17.00	Dirt road, 30 lks. wide, bears E. and W.
19.20	Spur, slopes S. 45° W.; desc. 5 ft. over NW. slope.
21.96	Point for the NE 1/16 sec. cor. of sec. 4, at intersection with the E. and W. center line of the NE¼.