

300

16358

Subdivision of Section 4, T. 25 S., R. 1 W.,
Willamette Meridian, Oregon

CHAINS	
3.10	Leave timber, enter logged area, edge bears E. and W.
13.50	Dirt road, 10 lks. wide, bears E. and W.
14.10	Ravine, drains N. 80° W.; asc. 20 ft. over SW. slope.
20.59	Point for the SW 1/16 sec. cor. of sec. 4, at intersection with the E. and W. center line of the SW¼.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	SW 1/16 S 4 1978
	from which
	An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 70¼° E., 23 lks. dist., with brass cap mkd. SW 1/16 S4 RM 1978 and an arrow pointing to the corner.
	An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 31¼° W., 13 lks. dist., with brass cap mkd. SW 1/16 S4 RM 1978 and an arrow pointing to the corner.
	Ascend 180 ft. over SW. slope.
27.20	Dirt road, 30 lks. wide, bears N. 45° W. and S. 45° E.
27.80	Ridge, bears N. 65° W. and S. 65° E.; desc. 275 ft. over NE. slope.
39.80	Ravine, drains E.; asc. 10 ft. over SE. slope.
41.18	The center W 1/16 sec. cor. of sec. 4.
	From the center S 1/16 sec. cor. of sec. 4.
	N. 88° 47' W., on the E. and W. center line of the SW¼ of sec. 4.
	Ascend 315 ft. over broken SE. slope, across logged area.
13.60	Spur ridge, bears N. and S.; desc. 180 ft. over SW. slope.
16.50	Gravelled road, 30 lks. wide, bears N. 30° W. and S. 40° E.
20.27	The SW 1/16 sec. cor. of sec. 4.
	Descend 245 ft. over broken SW. slope.
40.54	The S 1/16 sec. cor. of secs. 4 and 5.
	From the center W 1/16 sec. cor. of sec. 4.
	N. 3° 05' E., on the N. and S. center line of the NW¼ of sec. 4.
	Ascend 180 ft. over broken SE. slope, through heavy timber and dense undergrowth.