

Subdivision of Section 4, T. 25 S., R. 1 W.,  
Willamette Meridian, Oregon

CHAINS	
20.20	Top of ascent, slopes E.; desc. 10 ft. over NE. slope.
21.17	Point for the NW 1/16 sec. cor. of sec. 4, at intersection with the E. and W. center line of the NW¼.  Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.  NW 1/16 S 4 1978  from which  A fir, 8 ins. diam., bears S. 16¾° W., 68 lks. dist., mkd. NW 1/16 S4 BT.  No other suitable trees available within limits.  From this point, a corner established by Thomas E. Shrum, Jr., Registered Engineer No. 4287, in 1964, bears N. 65½° W., 0.20 chs. dist., monumented with an iron post, ¾ in. diam., loosely set, projecting 20 ins. above ground, with aluminum cap mkd. USPC T25S R1W NW1/16 SEC 4 RE 4287 1964, from which a bearing tree mkd. by Shrum:  A hemlock, 11 ins. diam., bears N. 19¾° W., 34 lks. dist., with scribe marks NW 1/16 S4 BT visible on open blaze.  Leave timber, enter logged area, edge bears N. and E.; desc. 60 ft. over NE. slope.
22.80	Ravine, drains E.; asc. 215 ft. over broken SE. slope.
26.20	Dirt road, 15 lks. wide, bears N. 80° E. and S. 40° W., in curve.
42.75	The W 1/16 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.
	From the center N 1/16 sec. cor. of sec. 4.  N. 89° 51' W., on the E. and W. center line of the NW¼ of sec. 4.  Descend 50 ft. over SW. slope, across logged area.
3.20	Creek, 3 lks. wide, course S. 10° E.; asc. 385 ft. over broken NE. slope.
20.235	The NW 1/16 sec. cor. of sec. 4.  Ascend 215 ft. over E. slope.
22.50	Gravelled road, 30 lks. wide, bears N. and S.
27.50	Ridge, bears N. and S.; desc. 365 ft. over SW. slope.
40.47	The N 1/16 sec. cor. of secs. 4 and 5.
	Subdivision of Section 19, T. 25 S., R. 1 W., Willamette Meridian, Oregon
	From the ¼ sec. cor. of secs. 19 and 30.  N. 0° 02' W., on the N. and S. center line of sec. 19.