

382

Subdivision of Section 19, T. 25 S., R. 1 W.,  
Willamette Meridian, Oregon

CHAINS	
	Descend 100 ft. over broken NE. slope, through heavy timber and dense undergrowth.
19.95	Point for the center S 1/16 sec. cor. of sec. 19.
	Set a brass tablet, 3¼ ins. diam., 3½ ins. stem, in drill hole, in exposed bedrock, with top mkd.
	<p style="text-align: center;">C S 1/16   S 19 C 1978</p>
	from which
	A fir, 3 ins. diam., bears N. 33° E., 66½ lks. dist., mkd. X BT.
	A boulder, 6 x 4 x 3 ft. above ground, bears N. 64° W., 6½ lks. dist., mkd. X B0.
	Descend 400 ft. over NE. slope.
32.30	Dirt road, 30 lks. wide, bears E. and W.
35.40	East Fork Rock Creek, 2 lks. wide, course N. 80° W.; asc. 25 ft. over SW. slope.
39.40	Dirt road, 30 lks. wide, bears N. 65° W. and S. 65° E.
39.90	Point for the center ¼ sec. cor. of sec. 19, at intersection with the E. and W. center line.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 25 S R 1 W C ¼ S 19 1978</p>
	from which
	A fir, 7 ins. diam., bears S. 75½° E., 53½ lks. dist., mkd. C ¼ S19 BT.
	A fir, 6 ins. diam., bears S. 83° W., 53½ lks. dist., mkd. C ¼ S19 BT.
	Ascend 480 ft. over broken SW. slope.
61.55	Spur, slopes S. 70° W.; asc. 75 ft. over broken SW. slope.
78.90	Spur, slopes S. 50° W.; desc. 40 ft. over NW. slope.
81.95	The ¼ sec. cor. of secs. 18 and 19.
	From the ¼ sec. cor. of secs. 19 and 20, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1967, monumented with an iron post, 1½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.
	<p style="text-align: center;">T 25 S R 1 W ¼ S 19   S 20 1967</p>