

Subdivision of Section 19, T. 25 S., R. 1 W.,
Willamette Meridian, Oregon

CHAINS	
	<p>from which the remains of the original bearing trees</p> <p>A cedar, 19 ins. diam., bears N. 85° E., 62 lks. dist., with fragmentary scribe marks visible on open blaze.</p> <p>A root hole, bears S. 72° W., 4 lks. dist., with a down fir alongside, 30 ins. diam., no marks visible.</p> <p>and bearing trees mkd. by Tracy</p> <p>A cedar, 19 ins. diam., bears S. 73° E., 59 lks. dist., with healed blaze.</p> <p>A chinquapin, 10 ins. diam., bears S. 39° W., 85 lks. dist., with healed blaze.</p> <p>N. 88° 55' W., on the E. and W. center line of sec. 19.</p> <p>Descend 360 ft. over SW. slope, across logged area.</p>
15.00	Creek, 1 lk. wide, course S. 15° W.; asc. 185 ft. over SE. slope.
19.50	Spur, slopes S.; desc. 440 ft. over broken SW. slope.
40.68	The center ¼ sec. cor. of sec. 19.
	Descend 75 ft. over SW. slope.
42.60	Dirt road, 30 lks. wide, bears N. 80° W. and S. 80° E.
49.30	East Fork Rock Creek, 5 lks. wide, course N. 80° W.; asc. 530 ft. over broken NE. slope.
73.50	Spur, slopes N. 20° E.; desc. 130 ft. over broken NW. slope.
89.20	Ravine, drains N. 20° E.; asc. 200 ft. over NE. slope.
97.55	Ridge, bears N. 20° W. and S. 20° E., also dirt road, 15 lks. wide, bears same as ridge; desc. 400 ft. over NW. slope.
105.95	Creek, 4 lks. wide, course N. 40° W.; asc. 360 ft. over broken NE. slope.
122.00	Point for the center 120 1/16 sec. cor. of sec. 19.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$C \frac{1/16}{S 19} 120$ <p style="text-align: center;">1978</p>
	<p>from which</p> <p>A hemlock, 5 ins. diam., bears S. 48° E., 22 lks. dist., mkd. C 120 1/16 S19 BT.</p> <p>A hemlock, 5 ins. diam., bears N. 30½° W., 15 lks. dist., mkd. C 120 1/16 S19 BT.</p> <p>Ascend 10 ft. over NE. slope.</p>