

384

Subdivision of Section 19, T. 25 S., R. 1 W.,
Willamette Meridian, Oregon

CHAINS	
124.55	Ravine, drains N. 15° E.; asc. 40 ft. over NE. slope.
130.15	Spur, slopes N.; desc. 120 ft. over broken NW. slope.
138.04	The $\frac{1}{4}$ sec. cor. of sec. 19 only, on the E. bdy. of T. 25 S., R. 2 W.
	From the 120 1/16 sec. cor. of secs. 19 and 30.
	N. 0° 12' W., on the N. and S. 120 line of the SW $\frac{1}{4}$ of sec. 19.
	Ascend 55 ft. over broken SE. slope, through heavy timber and dense undergrowth.
15.40	Top of ascent, slopes E.; desc. 165 ft. over broken NE. slope.
20.35	Point for the S 120 1/16 sec. cor. of sec. 19, at intersection with the E. and W. center line of the SW $\frac{1}{4}$.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.
	$\begin{array}{c} \text{S } \frac{1}{16} \\ \text{S } 19 \\ 1978 \end{array} \text{---} 120$
	from which
	A hemlock, 20 ins. diam., bears N. 71 $\frac{1}{2}$ ° W., 39 lks. dist., mkd. S 120 1/16 S19 BT.
	A hemlock, 18 ins. diam., bears S. 27 $\frac{1}{2}$ ° E., 11 lks. dist., mkd. S 120 1/16 S19 BT.
	Descend 600 ft. over broken NE. slope.
40.70	The center 120 1/16 sec. cor. of sec. 19.
	From the center S 1/16 sec. cor. of sec. 19.
	N. 89° 12' W., on the E. and W. center line of the SW $\frac{1}{4}$ of sec. 19.
	Ascend 85 ft. over broken NE. slope, through heavy timber and dense undergrowth.
3.50	Spur, slopes N.; desc. 100 ft. over NW. slope.
8.00	Ravine, drains N.; asc. 560 ft. over broken NE. slope.
38.50	Ridge, bears N. 45° W. and S. 45° E.; desc. 445 ft. over SW. slope.
51.20	Creek, 2 lks. wide, course N. 15° E.; asc. 200 ft. over NE. slope.
58.00	Spur, slopes N.; desc. 180 ft. over NE. slope.
62.00	Creek, 2 lks. wide, course N. 15° E.; asc. 590 ft. over broken NE. slope.
81.27	The S 120 1/16 sec. cor. of sec. 19.