

Subdivision of Section 19, T. 25 S., R. 1 W.,
Willamette Meridian, Oregon

<p>CHAINS</p> <p>87.25</p> <p>97.31</p>	<p>Ascend 170 ft. over NE. slope.</p> <p>Ridge, bears N. 20° W. and S. 20° E.; desc. 310 ft. over broken NW. slope.</p> <p>The S 1/16 sec. cor. of sec. 19 only, on the E. bdy. of T. 25 S., R. 2 W.</p>
<p>Remonumentation of Certain Original Corner Points, T. 25 S., R. 1 W., Willamette Meridian, Oregon</p>	
<p>The following field notes describe the remonumentation of certain original corner points, township 25 south range 1 west, Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group Number 350 Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, with New Accessories when Needed".</p> <p>The remonumentation of original corner points was made at the request of the Roseburg District Manager, for administrative purposes of the Bureau of Land Management.</p>	
<p>South Boundary, T. 25 S., R. 1 W., Willamette Meridian, Oregon</p>	
<p>(Remonumenting a corner established by Hezekiah H. Johnson, U. S. Deputy Surveyor, in 1900, and rehabilitated by Fred Mensch, U. S. Deputy Surveyor, in 1910)</p> <p>The ¼ sec. cor. of sec. 32 only, on the S. bdy. of the Tp., monumented with the original sandstone, 20 x 12 x 4 ins., loosely set, projecting 10 ins. above ground, and in a mound of stone, 2 ft. base, 1 ft. high, with fragmentary marks visible on N. face, from which a bearing tree mkd. by Mensch:</p> <p>A fir, 55 ins. diam., bears N. 41½° E., 130 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, to solid rock, mkd. X, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 25 S R 1 W ¼ S 32 1978</p> <p>from which new bearing trees</p> <p>A fir, 17 ins. diam., bears N. 80½° E., 53 lks. dist., mkd. ¼ S32 BT.</p> <p>A fir, 18 ins. diam., bears N. 5° W., 60½ lks. dist., mkd. ¼ S32 BT.</p> <p>Deposit corner stone alongside iron post.</p>	
<p>Subdivisions, T. 25 S., R. 1 W., Willamette Meridian, Oregon</p>	