

Remonumentation of Certain Original Corner Points,
T. 25 S., R. 1 W., Willamette Meridian, Oregon

CHAINS

(Remonumenting corners established by Hezekiah H. Johnson
U. S. Deputy Surveyor, in 1900)

The cor. of secs. 25, 26, 35, and 36, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1966, and further perpetuated by Gary L. Langlitz, Deputy County Surveyor, in 1974, monumented with the original corner tree, a hemlock, 8 ins. diam., with healed blaze on N., S., E., and W. faces, from which the remains of the original bearing trees:

A hemlock, 17 ins. diam., bears N. 89° E., 3 lks. dist., with fragmentary scribe marks visible on open blaze.

A hemlock root crown, size indeterminate, bears S. 51° E., 22 lks. dist.

and the remains of bearing trees mkd. by Tracy

A fir, 16 ins. diam., bears S. 41° E., 74 lks. dist., with fragmentary scribe marks visible on open blaze.

A chinquapin stump, 11 ins. diam., bears N. 83½° W., 102½ lks. dist., with scribe marks T25S R1W S26 CS BT visible on open blaze.

and a bearing tree mkd. by Langlitz

A hemlock, 12 ins. diam., bears N. 51° E., 63 lks. dist., with fragmentary scribe marks visible on open blaze.

and a reference monument and a new bearing tree

An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 68° W., 27 lks. dist., with brass cap mkd. T25S R1W S35 RM 1978 and an arrow pointing to the corner.

A hemlock, 6 ins. diam., bears N. 25½° W., 25 lks. dist., mkd. T25S R1W S26 BT.

The ¼ sec. cor. of secs. 11 and 12, perpetuated and recorded by G. Robert Lecklider, Registered Engineer No. 4079, in 1960, mkd. X ¼ on exposed bedrock, from which the remains of the original bearing tree:

A cedar snag, 5 ins. diam., bears S. 89° W., 15 lks. dist., with fragmentary scribe marks visible on open blaze.

and the remains of a bearing tree mkd. by Lecklider

A cedar stump, 15 ins. diam., bears S. 38° W., 13½ lks. dist., with scribe marks ¼ S11 RE 4079 BT visible on open blaze.

At the corner point

Seat a brass tablet, 3¼ ins. diam., 3½ ins. stem, in drill hole, in bedrock, with top mkd.