

Remonumentation of Certain Original Corner Points,  
T. 25 S., R. 1 W., Willamette Meridian, Oregon

CHAINS

T 25 S R 1 W

$$\begin{array}{c} \frac{1}{4} \\ S 11 | S 12 \\ 1978 \end{array}$$

from which a new bearing tree

A cedar, 18 ins. diam., bears S. 40° W., 69 lks.  
dist., mkd.  $\frac{1}{4}$  S11 BT.

No suitable tree available in sec. 12.

The cor. of secs. 22, 23, 26, and 27, perpetuated and re-  
corded by Thomas E. Shrum, Jr., Registered Engineer No.  
4287, in 1963, monumented with an iron post, 1 in. diam.,  
firmly set, projecting 4 ins. above ground, with aluminum  
cap mkd.

T 25 S R 1 W

$$\begin{array}{c} S 22 | S 23 \\ S 27 | S 26 \\ 1963 \end{array}$$

from which an original bearing tree

A cedar, 28 ins. diam., bears N. 31° W., 51 lks.  
dist., with fragmentary scribe marks visible  
on open blaze.

and the remains of a bearing tree mkd. by Shrum

A fir snag, 10 ins. diam., bears N. 42 $\frac{1}{2}$ ° E., 34 $\frac{1}{2}$   
lks. dist., with scribe marks 23 S BT visible  
on open blaze.

and new bearing trees

A cedar, 9 ins. diam., bears N. 48 $\frac{1}{2}$ ° E., 47 lks.  
dist., mkd. T25S R1W S23 BT.

A hemlock, 6 ins. diam., bears S. 79 $\frac{1}{2}$ ° E., 85 $\frac{1}{2}$   
lks. dist., mkd. T25S R1W S26 BT.

A yew, 6 ins. diam., bears S. 59 $\frac{1}{2}$ ° W., 104 lks.  
dist., mkd. T25S R1W S27 BT.

The  $\frac{1}{4}$  sec. cor. of secs. 14 and 15, perpetuated and re-  
corded by Milo E. Godfrey, Deputy County Surveyor, in  
1962, monumented with a mound of stone, 2 ft. base, 1 ft.  
high, from which the remains of the original bearing  
trees:

A cedar, 24 ins. diam., bears N. 46° E., 22 lks.  
dist., with fragmentary scribe marks visible  
on decayed blaze and scribe marks WC  $\frac{1}{4}$  S14 CS BT  
visible on open blaze. (Remarked by Godfrey)

A hemlock stump, 11 ins. diam., bears S. 68° W.,  
21 lks. dist., with scribe marks BT visible on  
open blaze. (Record, S. 63° W.)

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T 25 S R 1 W

$$\begin{array}{c} \frac{1}{4} \\ S 15 | S 14 \\ 1978 \end{array}$$

from which a new bearing tree

A pine, 5 ins. diam., bears N. 59 $\frac{1}{2}$ ° W., 26 lks.  
dist., mkd.  $\frac{1}{4}$  S15 BT.