

County Surveyor's Record, Douglas County, Oregon

FEET

MINERAL SURVEY NO. 987

~~CHAINS~~

Set an iron pipe, 42 ins. long, 2 ins. diam.,
38 ins. in the ground, with cap mkd. SP-1-987;
from which

The 1/4 sec. cor. of secs. 13 and 14,
T. 28 S., R. 4 W., Willamette Meridian,
Bears S. 64° 31' W., 405.58 ft. dist.,
hereinafter described.

A red cedar, 10 ins. diam., bears
S. 6° 05' W., 27.3 ft. dist., mkd.
SP-1-987 BT.

A fir, 18 ins. diam., bears N. 26° 25' W.,
22.2 ft. dist., mkd. SP-1-987 BT.

A corner of the location bears
S. 87° 40' W., 102.66 ft. dist.

Thence North

42.00	Ravine, drains N. 60° E.
82.00	Small ridge, bears N. 35° E. and S. 50° W.
146.00	Ravine, drains N. 70° E.
372.00	Skid road, 10 ft. wide, bears N. 65° E. and S. 50° W.
478.00	Creek, 1 ft. wide, course N. 80° E.
515.00	Skid road, 10 ft. wide, bears S. 65° E. and N. 77° W.
616.10	Cor. No. 2
	Set an iron pipe, 42 ins. long, 2 ins. diam., 36 ins. in the ground, with cap mkd. SP-2-987; from which
	A fir, 7 ins. diam., bears S. 9 1/4° W., 34.1 ft. dist., mkd. SP-2-987 BT.
	A fir, 14 ins. diam., bears N. 60 3/4° W., 16.4 ft. dist., mkd. SP-2-987 BT.
	A corner of the location bears N. 53° 33' W., 164.69 ft. dist.
	Thence N. 89° 26' E.
78.00	Skid road, 10 ft. wide, bears N. 60° W. and S. 60° E.
567.00	Steep descent
886.00	Foot of hill and center of mining ditch, 30 ft. average width, 16 ft. average depth, drains S. 20° E.
1089.00	North Myrtle Creek, 10 ft. wide, course S.
1192.00	Service power line, bears N. 35° E. and S. 35° W.