

County Surveyor's Record, Douglas County, Oregon

16377

Dependent Resurvey of a Portion of the South Boundary,
T. 24 S., R. 4 W., Willamette Meridian, Oregon.

CHAINS

(Restoring the survey by Harvey Gordon and
Charles Gardner, U. S. Deputy Surveyors,
in 1855)

Beginning at the cor. of secs. 3, 4, 33, and 34, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1961, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap marked

COUNTY SURVEYORS OFFICE

T 24 S
S 33 | S 34
S 4 | S 3
T 25 S
1961

from which the remains of the original bearing trees

A sawed fir stump, 60 ins. diam., bears S. 51° W., 212 lks. dist., with fragmentary scribe marks visible on bark blaze.

A fir, 48 ins. diam., bears N. 78° W., 172 lks. dist., with fragmentary scribe marks visible on bark blaze.

and the remains of bearing trees mkd. by Byron

A sawed fir stump, 24 ins. diam., bears N. 2° E., 17 1/2 lks. dist., with healed blaze.

A fir, 20 ins. diam., bears S. 26 1/2° E., 34 lks. dist., with healed blaze.

A fir, 16 ins. diam., bears S. 55° W., 35 lks. dist., with healed blaze

A fir, 22 ins. diam., bears N. 37 1/2° W., 44 1/2 lks. dist., with healed blaze.

and a new bearing tree

A fir, 10 ins. diam., bears N. 32 1/2° E., 38 lks. dist., mkd. T24S R4W S34 BT.

N 89° 44' W., bet. secs. 4 and 33, marking and blazing the true line.

Ascend 325 ft. over SE slope, through heavy timber and dense undergrowth.

- 15.80 Ridge, bears N. 25° E. and S. 25° W.; desc. 410 ft. over broken NW slope.
- 35.00 Ravine, drains N. 70° W.: desc. 25 ft. over NW slope.
- 37.50 Bottom of descent, slopes NW.; asc. 35 ft. over NE slope.
- 39.85 Spur, slopes NW; desc. 2 ft. over NW slope.
- 39.98 Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original corner.