

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the South Boundary  
T. 24 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

*FD OK  
12/15  
H. CHRISTENSEN  
M 123-25 A/B*

T 24 S R 4 W  
1/4 S 33  
S 4  
T 25 S R 4 W  
1979

from which

A fir, 22 ins. diam. bears N. 23° E., 6 lks. dist., mkd.  
1/4 S33 BT.

A fir, 13 ins. diam., bears S. 52 1/2° E., 40 lks. dist.,  
mkd. 1/4 S4 BT.

Descend 65 ft. over NW slope.

42.50 Creek, 1 lk. wide, course N. 20° W.: asc. 80 ft. over NE slope.

46.00 Spur, slopes N.; desc. 15 ft. over NW slope.

47.70 Ravine, drains N.; asc. 50 ft. over NE slope.

53.35 Spur, slopes N.; desc. 230 ft. over NW slope.

79.96 The cor. of secs. 4, 5, 32, and 33, perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1963, monumented with and iron post, 1 1/4 ins. diam. firmly set, projecting 10 ins. above ground, with brass cap mkd.

*FD OK 8/92  
D. PEEL M 115-62*

COUNTY SURVEYORS OFFICE  
T 24 S  
S 32 | S 33 R 4 W  
S 5 | S 4  
T 25 S  
1963

from which the remains of the original bearing trees

A white oak, 50 ins. diam., bears S. 54 1/2° E., 332 lks. dist., with healed blaze.

A decayed oak stump, 25 ins. diam., bears S. 53 1/2° W., 195 lks. dist., no marks visible.

A white oak, 30 ins. diam. bears N 38 1/2° W., 84 lks, dist., with fragmentary scribe marks visible on open blaze.

and bearing trees mkd. by Godfrey

A white oak, 10 ins. diam. bears N. 60° E., 29 lks. dist., with healed blaze.

A fir, 10 ins. diam., bears S. 14° E., 70 1/2 lks. dist., with healed blaze.

A white oak, 6 ins. diam., bears S. 41 1/2° W., 43 1/2 lks. dist., with fragmentary scribe marks visible on open blaze.

A fir, 14 ins. diam., bears N. 24° W., 83 1/2 lks. dist., with healed blaze.

Land, mountainous.