

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the South Boundary
T. 24 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

Soil, rocky clay.
Timber, fir, hemlock, cedar, maple, oak, madrone, myrtle, elder, and chinquapin; undergrowth, vine maple, poison oak, salal, rhododendron, Oregon grape, and fern.

Dependent Resurvey of a Portion of the South Boundary,
T. 23 S., R. 4 W., Willamette Meridian, Oregon.

(Restoring the survey by Harvey Gordon and Charles Gardner, U.S. Deputy Surveyor, in 1855)

From the cor. of secs. 32 and 33 only, perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1963, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 23 S
S 32 | S 33
R 4 W
1963

*FD OK BY D. E. GARDNER
7/24/64 11-9-60*

from which the remains of the original bearing trees

A sawed fir stump, 48 ins. diam., bears N. 70° E.,
42 lks., dist., no marks visible.

A sawed fir stump, 42 ins. diam., bears S. 86° E.,
45 lks. dist., no marks visible.

A sawed fir stump, 48 ins. diam., bears N. 43° W.,
38 lks. dist., with chaining notch visible on decayed blaze.

and the remains of bearing trees mkd. by Godfrey.

A sawed cedar stump, 20 ins. diam., bears S. 75° E.,
56 1/2 lks. dist., with healed blaze.

A fir, 54 ins. diam., bears N. 75 1/4° W., 99 lks.
dist., with healed blaze.

and a bearing tree mkd. by Jake Jelley, in 1976

A maple, 15 ins. diam., bears N. 77° E., 155 lks. dist.,
with scribe marks T23S R4W S33 BT visible on open blaze.

N. 89° 44' W., on the S. bdy. of sec. 32, marking and blazing the true line.

Ascend 10 ft. over NE slope, through heavy timber and dense undergrowth.

2.74 True point for the closing cor. of secs. 4 and 5, T. 24 S.,
R. 4 W., hereinafter described.

Ascend 5 ft. over NE slope.

4.90 Ravine, drains N.: asc. 15 ft. over NE slope

7.80 Spur, slopes N. 40° W.: desc. 410 ft. over NW slope.