

County Surveyor's Record, Douglas County, Oregon

16380

Dependent Resurvey of a Portion of the South Boundary,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

40.01

Point for the 1/4 sec. cor. of secs. 5 and 32 at proportionate distances; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stones, 3 ft. base, to top with brass cap mkd.

*FD OK
BY D. Baker
9-7-4 M119-40*

T 23 S R 4 W
1/4 $\frac{S 32}{S 5}$
T 24 S R 4 W
1979

from which

A fir, 6 ins. diam., bears N. 13° E., 43 lks. dist., mkd. 1/4 S32 BT.

An oak, 12 ins. diam., bears S 32° W., 95 1/2 lks. dist., mkd. 1/4 S5 BT.

Set a 5 ft. steel fence post alongside iron post.

Descend 10 ft. over NW slope.

41.35

Dry creek bed, 3 lks. wide, drains NW; asc. 100 ft. over NE slope.

48.30

Ridge, bears N. 20° W. and S. 20° E: desc. 270 ft. over SW slope.

66.90

Ravine, drains NW; asc. 50 ft. over NE slope.

69.70

Power transmisson line, bears N. 40° E. and S. 40° W.

70.00

Top of ascent, slopes NW; desc. 130 ft. over SW slope.

72.85

Power transmission line, bears N. 40° E. and S. 40° W.

79.90

Creek, 5 lks. wide, course N.; asc. 3 ft. over NE. slope.

80.02

The cor. of secs. 5, 6, 31, 32, perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1963, monumented with an iron post, 1 1/4 ins. diam. firmly set, projecting 8 ins. above ground, in a mound of stones, 3 ft. base, to top with brass cap mkd.

*FD OK PER DOLAN
DEC. 1969 M107-32*

COUNTY SURVEYORS OFFICE

T 23 S
 $\frac{S 31 | S 32}{S 6 | S 5}$ R 4 W
T 24 S
1963

from which the remains of an original bearing tree

A root hole, bears S 45° E., 132 lks, dist., with a down maple alongside, 25 ins. diam. no marks visible.

and bearing trees mkd. by Godfrey

A cedar, 12 ins. diam., bears N. 63° E., 132 lks. dist., with healed blaze.

A fir, 18 ins. diam., bears S. 10° E., 54 lks. dist., with healed blaze.