

# County Surveyor's Record, Douglas County, Oregon

16381

Dependent Resurvey of a Portion of the South Boundary  
T. 23 S., R. 4 W., Willamette Meridian, Oregon

**CHAINS**

A cedar, 23 ins. diam., bears S. 39° W., 32 lks. dist.,  
with healed blaze.

A cedar, 11 ins. diam., bears N. 48° W., 198 lks. dist.,  
with healed blaze.

Land mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, maple, oak, myrtle, dogwood, chinqua-  
pin, and alder; undergrowth, vine maple, poison oak, salal, Oregon  
grape, rhododendron, and fern.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 4 W., Willamette Meridian, Oregon

(Restoring the survey by Harvey Gordon and Charles  
Gardner, U. S. Deputy Surveyors, in 1855, and the  
Survey by Oscar Thiel, U.S. Deputy Surveyor, in  
1896-97)

From the cor. of secs. 14, 15, 22 and 23, monumented with an iron  
post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above  
ground, with brass cap mkd.

T 24 S R 4 W  
S 15 | S 14  
S 22 | S 23  
1963

*Fd 8/30  
MINE II*

from which bearing trees mkd. by White and McDonald

A fir, 19 ins. diam., bears N. 74° E., 88 lks. dist.,  
with healed blaze.

An oak, 16 ins. diam., bears S. 86 1/2° E., 116 lks.  
dist., with fragmentary scribe marks visible on partially  
open blaze.

A cedar, 36 ins. diam., bears N. 41° W., 654 lks. dist.,  
with healed blaze.

No suitable trees available within limits in sec. 22.

N. 0° 09' W., bet. secs. 14 and 15, marking and blazing the true  
line.

Ascend 220 ft. over SW slope, through scattering timber and dense  
undergrowth.

19.00 Woven wire fence, extends E. and W.

19.50 Ridge, bears E. and W.; desc. 2 ft. over NE slope.

19.99 Point for the S 1/16 sec. cor. of secs 14 and 15.

Set an iron post, 28 ins. long 2 1/2 ins. diam., 24 ins. in the  
ground, with brass cap mkd.

S 1/16  
S 15 | S 14  
1979

from which