

County Surveyor's Record, Douglas County, Oregon

16382

Dependent Resurvey Portion of Subdivisional Lines,
T. 24 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A fir, 11 ins. diam., bears N. 36° E., 56 lks. dist.,
mkd. S 1/16 S 14 BT.

A madrone, 13 ins. diam., bears N. 57 1/2° W., 14 lks.
dist., mkd. S 1/16 S 15 BT on bark.

Descend 130 ft. over broken NE slope.

39.98

The 1/4 sec. cor. of secs. 14 and 15, perpetuated and recorded
by Vernon R. Tracy, Deputy County Surveyor, in 1963, monumented
with an iron post, 1 1/4 ins. diam., firmly set, projecting 9 ins.
above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 24 S
1/4 S 15 S 14
R 4 W
1963

from which the remains of an original bearing tree

A fir snag, 26 ins. diam., bears S. 78° E., 34 lks.
dist., with scribe marks 1/4 S visible on bark blaze.

and bearing trees mkd. by Tracy

A fir, 13 ins. diam., bears N. 32 1/2° E., 8 lks. dist.,
with healed blaze.

A fir, 13 ins. diam., bears S. 20° E. 68 lks. dist.,
with healed blaze.

and a new bearing tree

A fir, 7 ins. diam., bears N. 21 1/4° W., 42 1/2 lks. dist.,
mkd. 1/4 S 15 BT.

N. 0° 11' W., beginning new measurement.

Descend 190 ft. over N. slope.

7.20

Dirt road, 25 lks. wide, bears N. 70° E., and S. 70° W.

10.70

Creek, 3 lks. wide, course N. 70° E.; asc. 180 ft. over SE slope.

20.15

Spur, slopes N. 70° E.; desc. 175 ft. over NE slope.

31.20

Wet ravine, drains N. 60° E., asc. 25 ft. over SE slope

33.50

Spur, slopes N. 60° E.; desc. 80 ft. over NE slope.

35.65

Wet ravine, drains E.; desc. 15 ft. over NE slope.

36.90

Dirt road, 25 lks. wide, bears N. 40° W. and S. 40° E.

39.30

Boyd Creek, 4 lks. wide, course S. 55° E.; asc. 20 ft. over
NW slope.

39.94

The cor. of secs. 10, 11, 14 and 15, perpetuated and recorded
by James W. Byron, Deputy County Surveyor, in 1958, and further
perpetuated and recorded by Milo E. Godfrey, Deputy County
Surveyor, in 1963, monumented with an iron post, 1 1/4 ins. diam.,
firmly set, projecting 10 ins. above ground, with brass cap mkd.