

County Surveyor's Record, Douglas County, Oregon

16283

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

T 24 S
S 10 | S 11
S 15 | S 14
R 4 W
1958

from which the remains of an original bearing tree

A sawed fir stump, 26 ins. diam., bears S. 56 1/4° W.,
52 lks. dist., with fragmentary scribe marks visible
on open blaze. (Record, S. 58° W.)

and the remains of bearing trees mkd. by Godfrey

A hemlock, 12 ins. diam., bears N. 25° E., 128 lks.
dist., with healed blaze.

A sawed cedar stump, 45 ins. diam., bears S. 22° E.,
402 lks, dist., with healed blaze.

A cedar, 14 ins. diam., bears S. 66° W., 300 lks. dist.,
with healed blaze.

and new bearing trees

A fir, 6 ins. diam., bears N. 38° E., 43 1/2 lks. dist.,
mkd. T24S R4W S11 BT.

A fir, 9 ins. diam., bears S. 64 1/2° E., 124 lks. dist.,
mkd. T24S R4W S14 BT.

A fir, 9 ins. diam., bears N. 17 3/4° W., 36 1/2 lks. dist.,
mkd. T24S R4W S10 BT.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, maple, oak, madrone, alder, and
chinquapin; undergrowth, salal, poison oak, vine maple, rhododen-
dron, Oregon grape, and fern.

From the corner of secs. 3, 4, 33, and 34, on the S. bdy. of the
Tp.

N. 0° 20' E., bet. secs.33 and 34.

Ascend 310 ft. over broken SE slope, through heavy timber and
dense undergrowth.

20.70 Ridge, bears N. 60° E. and S. 60° W.; desc. 180 ft. over NE slope.

34.05 Ravine, drains N. 40° W.; desc. 100 ft. over NE slope.

36.95 Ravine, drains N. 40° W.; desc. 15 ft. over NW slope.

39.68 The 1/4 sec. cor. of secs. 33 and 34, perpetuated and recorded
by Vernon R. Tracy, Deputy County Surveyor, in 1963, monumented
with an iron post, 1 1/4 ins. diam., firmly set, projecting 10
ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

1/4
S 33 | S 34
1963

from which the remains of an original bearing tree