

County Surveyor's Record, Douglas County, Oregon

16384

Dependent Resurvey, Portion of Subdivisional lines,
T. 24 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A decayed fir stump, 14 ins. diam., bears N. 30° E., 41 lks. dist., no marks visible (Record, 38 lks.)

and bearing trees mkd. by Tracy

A fir, 27 ins. diam., bears S. 25° E., 39 lks. dist., with healed blaze.

A fir, 27 ins. diam., bears S. 28° W., 58 lks. dist., with healed blaze.

N. 0° 14' E., beginning new measurement.

Ascend 90 ft. over SW slope.

5.05 Spur, slopes N. 45° W.; desc. 100 ft. over NW slope.

8.50 Creek, 2 lks. wide, course N. 65° W.; asc. 95 ft. over SW slope.

14.40 Spur, slopes N. 70° W.; desc. 45 ft. over broken NW slope.

19.90 Spur, slopes N. 45° W.; desc. 275 ft. over NE slope.

40.81 The cor. of secs. 27, 28, 33, and 34, perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1963, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 24 S
S 28 | S 27
S 33 | S 34
R 4 W
1963

from which the remaining original bearing trees

An oak, 20 ins. diam., bears S 10° W., 87 lks. dist., with healed blaze.

An oak, 23 ins. diam., bears N. 77° W., 156 lks. dist., with healed blaze. (Record, N 80° W.)

and the remains of bearing trees mkd. by Godfrey

A sawed fir stump, 18 ins. diam., bears N. 50° E., 30 1/2 lks. dist., with healed blaze.

A fir, 15 ins. diam., bears S. 57 1/2° E., 23 lks. dist., with healed blaze.

A fir, 17 ins. diam., bears S. 38 1/2° W., 33 1/2 lks. dist., with healed blaze.

An oak, 10 ins. diam., bears N. 89° W., 15 lks. dist., with healed blaze.

No suitable tree available within limits in sec. 27.

Land, mountainous.

Soil rocky clay loam.

Timber, fir, hemlock, cedar, maple, oak, alder, live oak, and chinquapin; undergrowth, salal, rhododendron, vine maple, poison oak, Oregon grape, and fern.