

Dependent Resurvey, Portion of Subdivision Lines,
T. 24 S., R. 4 W., Willamette Meridian, Oregon.

CHAINS

From the cor. of secs. 14, 15, 22, and 23.

S. 89° 37' W., bet. secs. 15 and 22.

Ascend 55 ft. over E. slope, through scattering timber and dense undergrowth.

4.54 The exterior cor. on the E. bdy. of Donation Land Claim No 46, reestablished at proportionate distance and recorded by Donald A Bentz, Registered Land Surveyor No. 839, in 1979, and is accepted as the best available evidence of the position of the original corner, monumented with an iron rod, 5/8 ins. diam., firmly set, projecting 6 ins. above ground.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 S R 4 W
DLC 46 | S 15
S 22
1979

from which

An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 85 1/2° E., 62 lks. dist., with brass cap mkd. T24S R4W S15 RM 1979 and an arrow pointing to the corner.

An oak, 5 ins. diam., bears N. 69 1/4° W., 42 lks. dist., mkd. C 46 BT.

Reset iron rod alongside iron post.

S. 89° 37' W., beginning new measurement.
Ascend 2 ft. over SE slope.

0.75 Ridge, bears N. and S.; desc. 230 ft. over broken W. slope.

15.35 Point for the E 1/16 sec. cor. of secs. 15 and 22.

Set an iron post, 28 ins. long 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16 $\frac{S 15}{S 22}$
1979

from which

An oak, 8 ins. diam., bears N. 45 1/4° E., 38 lks. dist., mkd. E 1/16 S15 BT.

A fir, 9 ins. diam., bears S. 67 3/4° E., 110 lks. dist., mkd. E 1/16 S22 BT.

Descend 210 ft. over SW slope.