

County Surveyor's Record, Douglas County, Oregon

16386

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

30.52 The interior cor. on the E. bdy. of Donation Land Claim No 46, reestablished at proportionate distance and recorded by Donald A. Bentz, Registered Land Surveyor, No 839, in 1979, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, from which a bearing tree mkd. by Bentz:

An oak, 18 ins. diam., bears N. 88° E., 39 1/2 lks. dist., with scribe marks T24S R4W BT visible on open blaze.

Descend 5 ft. over SW slope.

35.24 The 1/4 sec. cor. of secs. 15 and 22, reestablished at proportionate distance and recorded by Donald A. Bentz, Registered Land Surveyor No. 839, in 1978, and is accepted as the best available evidence of the position of the original corner, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 8 ins. above ground, from which bearing trees mkd. by Bentz:

A black oak, 14 ins. diam. bears N. 89 1/2° W., 166 lks. dist., with scribe marks 1/4 S15 T24S R4W BT visible on open blaze.

A fir, 7 ins. diam., bears S. 36° W., 134 lks. dist., with scribe marks 1/4 S22 T24S R4W BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 S R 4 W
1/4 S 15
S 22
1979

Reset iron rod alongside iron post.

S. 89° 37' W., beginning new measurement.

Descend 50 ft. over broken SW slope.

6.40 Creek, 2 lks. wide, course S. 45° W.; asc. 100 ft. over SE Slope.

10.80 Top of ascent, slopes S.; desc. 50 ft. over SW slope.

18.80 Creek, 3 lks. wide, course S.; asc. 160 ft. over SE slope.

24.80 Spur, slopes S.; desc. 100 ft. over SW slope.

35.65 Dirt road, 10 lks. wide, bears N. and S.

39.78 The cor. of secs. 15, 16, 21, and 22, perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1963, monumented with an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above ground, from which the remains of the original bearing trees:

A white oak, 37 ins. diam., bears S. 8 1/4° E., 455 lks, dist., with open blaze, no marks visible.