

County Surveyor's Record, Douglas County, Oregon

16387

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A black oak snag, 24 ins. diam., bears N. 2 1/2° W.,
1391 lks. dist., with fragmentary scribe marks in reverse
and relief visible on overgrowth, and remarked by Godfrey,
with fragmentary scribe marks visible on open blaze.

and bearing trees mkd. by Godfrey

An ash, 17 ins. diam., bears N. 49° E., 97 lks. dist., with
fragmentary scribe marks visible on open blaze.

A white oak, 15 ins. diam., bears S. 32° E., 256 lks, dist.,
with healed blaze.

A white oak, 15 ins. diam., bears S. 10° W., 491 lks. dist.,
with healed blaze.

An ash, 8 ins. diam., bears N. 7° W., 234 lks. dist., with
fragmentary scribe marks visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the
ground, with brass cap mkd.

T 24 S R 4 W
S 16 S 15
S 21 S 22
1979

FD. OK. 2/23/93
D.C.S.P.
C.S. 64/39

Reset iron pipe alongside iron post.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, oak, madrone, alder, myrtle, and
chinquapin; undergrowth, salal, poison oak, vine maple, rhododendron
Oregon grape, and fern.

N. 0° 23' W., bet. secs. 15 and 16.

Ascend 200 ft. over SW slope, through heavy timber and dense under-
growth.

11.75 Head of ravine, drains S. 45° W.; asc. 225 ft. over S. slope.

39.74 The 1/4 sec. cor. of secs. 15 and 16, monumented with an iron post
2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with
brass cap mkd.

1/4
S 16 S 15
T 24 S R 4 W
1963

from which the remains of the original bearing trees

A root hole, bears N. 46° E., 80 lks, dist., with a down
oak alongside, 30 ins. diam., with fragmentarty scribe
marks visible on open blaze.

An oak, 27 ins. diam., bears N. 41° W., 53 lks. dist., with
fragmentary scribe marks visible on open blaze.