

County Surveyor's Record, Douglas County, Oregon

16388

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>and bearing trees mkd. by White and McDonald</p> <p style="padding-left: 40px;">A fir, 21 ins. diam, bears S. 26° E., 26 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears S. 78 1/2° W., 15 lks. dist., with healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 12' W., beginning new measurement.</p> <p>Ascend 390 ft. over SE slope.</p>
12.20	Ridge bears N. 70° E. and S. 70° W.; desc. 45 ft. over NW slope.
16.55	Head of ravine, drains W.; asc. 20 ft. over broken SW slope.
19.975	<p>The N 1/16 sec. cor. of secs. 15 and 16, established and recorded by Donald A. Bentz, Registered Land Surveyor No. 839, in 1979, and is accepted as the corner, monumented with an iron rod, 5/8 ins. diam., firmly set, projecting 6 ins. above ground, from which bearing trees mkd. by Bentz:</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 25 1/4° E., 80 lks. dist. with scribe marks N 1/16 S15 BT visible on open blaze.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 88 1/2° W., 22 1/2 lks. dist., with scribe marks N 1/16 S16 BT visible on open blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 16 S 15 1979</p> <p style="padding-left: 40px;">Reset iron rod alongside iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 12' W., beginning new measurement.</p> <p>Ascend 100 ft. over SW slope.</p>
4.65	Ravine, drains S. 40° W.; asc. 290 ft. over SW slope.
18.60	Ridge, bears E. and W.; desc. 2 ft. over N. slope.
19.975	<p>The cor. of secs. 9, 10, 15, and 16, perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor No. 239, in 1960, and further perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1963, monumented with a T-shaped iron rod 1 in. diam., firmly set, projecting 4 ins. above ground, from which the remains of an original bearing tree:</p> <p style="padding-left: 40px;">A root hole, bears N. 70° W., 154 lks. dist., with a down fir alongside, 48 ins. diam., with fragmentary scribe marks visible on open blaze.</p> <p>and a bearing tree mkd by Haines</p>