

County Surveyor's Record, Douglas County, Oregon

16289

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 4 W., Willamette Meridian, Oregon.

CHAINS

A cedar, 24 ins. diam., bears N. 6° E., 47 1/2 lks. dist., with healed blaze.

and the remains of bearing trees mkd. by Godfrey

A fir snag, 23 ins. diam., bears S. 56° E., 99 lks. dist., with fragmentary scribe marks visible on open blaze.

A fir stump, 22 ins. diam., bears S. 55° W., 70 lks. dist., with healed blaze.

A grand fir, 20 ins. diam., bears N. 58° W., 105 1/2 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 S R 4 W
S 9 | S 10
S 16 | S 15
1979

from which new bearing trees

A fir, 9 ins. diam., bears S 55 1/4° E., 52 lks. dist., mkd. T24S R4W S15 BT.

A fir, 11 ins. diam., bears S. 25° W., 7 lks. dist., mkd. T24S R4W S16 BT.

Reset iron rod alongside iron post.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, maple, oak, madrone, alder, chinquapin, and myrtle; undergrowth, salal, rhododendron, vine maple, poison oak, Oregon grape, and fern.

From the cor. of secs. 10, 11, 14, and 15.

S. 89° 36' W., bet. secs. 10 and 15.

Descend 10 ft. over SW slope, through scattering timber and dense undergrowth.

- 1.10 Boyd Creek, 4 lks. wide, course S. 10° E.; asc. 280 ft. over NE slope.
- 2.35 Dirt road, 25 lks. wide, bears N. 75° W. and S. 75° E.
- 20.00 Spur, slopes N. 15° E.; desc. 25 ft. over NW slope.
- 21.50 Wet ravine, drains N. 30° E.; asc. 60 ft. over NE slope.
- 36.35 Creek, 2 lks. wide, course N. 15° E.; asc. 145 ft. over NE slope.
- 39.00 Spur, slopes N. 70° E.; desc. 5 ft. over NW slope.
- 39.80 The 1/4 sec. cor. of secs. 10 and 15, perpetuated and recorded by Wilford Haines, Registered Land Surveyor