

# County Surveyor's Record, Douglas County, Oregon

16390

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 24 S., R. 4 W., Willamette Meridian, Oregon

**CHAINS**

No. 239, in 1960, and further perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1963, monumented with a T-shaped iron rod, 1 in. diam., firmly set, projecting 6 ins. above ground, from which the remains of the original bearing trees:

A sawed fir stump, 30 ins. diam., bears N. 63 1/2° E., 13 lks. dist., with fragmentary scribe marks visible on open blaze.

A sawed fir stump, 30 ins. diam., bears S. 61° E., 23 lks. dist., with fragmentary scribe marks visible on open blaze.

and a bearing tree mkd. by Haines

A fir, 20 ins. diam., bears S. 23° W., 52 1/2 lks. dist., with fragmentary scribe marks visible on open blaze.

and a bearing tree mkd. by Godfrey

A hemlock, 10 ins. diam., bears N. 46° W., 48 1/2 lks., dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 S R 4 W  
1/4 S 10  
S 15  
1979

from which new bearing trees

A fir, 6 ins. diam., bears N. 72 1/2° W., 16 1/2 lks. dist., mkd. 1/4 S10 BT.

A fir, 5 ins. diam., bears S. 31 3/4° W., 16 lks. dist., mkd. X BT.

Reset iron rod alongside iron post.

S. 89° 19' W., beginning new measurement.

Descend 30 ft. over NW slope.

3.00 Bottom of descent, slopes N.; asc. 225 ft. over NE slope.

19.70 Point for the W 1/16 sec. cor. of secs. 10 and 15.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 S 10  
S 15  
1979

from which

A fir, 8 ins. diam., bears N. 4 1/2° W., 27 lks. dist., mkd. W 1/16 S10 BT.