

County Surveyor's Record, Douglas County, Oregon

16291

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 8 ins. diam., bears S. 58° E., 13 lks. dist., mkd. W. 1/16 S15 BT.</p> <p>Ascend 315 ft. over E. slope.</p>
31.60	Dirt road, 25 lks. wide, bears N. 40° W. and S. 40° E.
39.40	The cor. of secs. 9, 10, 15, and 16.
	<p>Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, maple, oak, madrone, myrtle, chinquapin, and alder; undergrowth, rhododendron, vine maple, salal, Oregon grape, poison oak, and fern.</p>
	N. 0° 10' E., bet. secs. 9 and 10.
	Descend 400 ft. over broken NE slope, through heavy timber and undergrowth.
14.15	Dirt road, 25 lks. wide, bears N. 60° W. and S. 30° E.
31.95	Creek, 1 lk. wide, course N. 45° E., desc. 60 ft. over NE slope.
40.15	<p>The 1/4 sec. cor. of secs. 9 and 10, perpetuated and recorded by Authur R. Evans, Registered Engineer No. 2741, in 1956, from original evidence no longer in existence, further perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor No. 239, in 1960, and further perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1963, monumented with a T-shaped iron rod, 1 in. diam., firmly set, projecting 8 ins. above ground, from which the remains of bearing trees mkd. by Evans:</p> <p>A root hole, bears S. 59 1/2° E., 90 1/2 lks. dist., with a down cedar alongside, 30 ins. diam., no marks visible.</p> <p>A root hole, bears N. 67 1/2° W., 57 1/2 lks. dist., with a down fir alongside, 36 ins. diam., no marks visible.</p> <p>and bearing trees mkd. by Godfrey</p> <p>A hemlock, 11 ins. diam., bears N. 43° E., 16 lks. dist., with healed blaze.</p> <p>A hemlock, 11 ins. diam., bears S. 46 1/2° W., 28 1/2 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 S R 4 W 1/4 S 9 S 10 1979</p> <p style="text-align: right;">FD OK 6-25-97 S. NESS CS 65115-4A</p> <p>Reset iron rod alongside iron post.</p>