

County Surveyor's Record, Douglas County, Oregon

16393

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 4 W., Willamette Meridian.

CHAINS

Timber, fir, hemlock, cedar, maple, oak, madrone, alder, and chinquapin; undergrowth, salal, vine maple, poison oak, rhododendron Oregon grape, and fern.

From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp.
N. 0° 22' E., bet. secs. 32 and 33.

Descend 90 ft. over general NE slope, through heavy timber and dense undergrowth.

24.00 Leave timber, enter open field, edge bears E. and W.

30.25 Driver Valley Road, paved, 30 lks. wide, bears N. 45° E. and S. 45° W.

37.90 Creek, 2 lks. wide, course S. 45° W.; asc. 5 ft. over nearly level open field.

40.18 The 1/4 sec. cor. of secs. 32 and 33, perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1963, determined at recorded bearing and distance from the remaining original bearing tree:

A white oak, 37 ins. diam., bears N. 25° E., 240 lks. dist., with fragmentary scribe marks visible on open blaze.

and bearing trees mkd. by Godfrey

A white oak, 9 ins. diam., bears N. 75° E., 223 lks. dist., with healed blaze.

An ash, 22 ins. diam., bears S. 24° W., 414 lks. dist., with healed blaze.

At corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 40 ins. in the ground, the top 12 ins. below the surface, with brass cap mkd.

T 24 S R 4 W
1/4
S 32 | S 33
1979

Set a steel fence post alongside iron post.

N 0° 12' E., beginning new measurement.

Ascend 325 ft. over SE slope, through open field.

40.12 The cor. of secs. 28, 29, 32, and 33, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1960, and further perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1970, monumented with an iron post, 1 1/4 ins. diam., loosely set, projecting 20 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 24 S
S 29 | S 28
S 32 | S 33
1960