

County Surveyor's Record, Douglas County, Oregon

16394

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

from which an original bearing tree

A white oak, 50 ins. diam., bears N. 25° E., 420 lks. dist.,
with scribe marks R4W visible on open blaze.

and bearing trees mkd. by Byron

A black oak, 30 ins. diam., bears N. 38 1/2° E., 372 lks.
dist., with healed blaze.

A white oak, 18 ins. diam., bears N. 83 1/2° E., 385 lks.
dist., with healed blaze.

and bearing objects recorded by Tracy

The SE corner of porch roof support of a concrete block
house, bears N. 4° E., 126 lks. dist.,

The NW corner of the house, bears N. 18° W., 167 lks. dist.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the
ground, with brass cap mkd.

T 24 S R 4 W
S 29 | S 28
S 32 | S 33
1979

Invert County iron post and reset alongside iron post.

No other suitable accessories available within the limits.

Corner is located on ridge, bears N. 30° E. and S. 30° W.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, maple, oak, madron, alder, and
chinquapin; undergrowth, salal, poison oak, vine maple, rhododendron
Oregon grape, and fern.

From the cor. of secs. 27, 28, 33, and 34.

S. 89° 21' W., bet. secs. 28 and 33.

Ascend 85 ft. over NE slope, through heavy timber and dense
undergrowth.

5.45 Ridge, bears N. 40° W., and S. 40° E.; desc. 165 ft. over W. slope.

31.30 Driver Valley Road, paved 30 lks. wide, bears N. 35° E. and S.
35° W., enter open field, edge bears same as road.

40.14 The 1/4 sec. cor. of secs. 28 and 33, perpetuated and recorded
by Milo E. Godfrey, Deputy County Surveyor, in 1963, monumented
with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins.
above ground, with brass cap mkd.