

County Surveyor's Record, Douglas County, Oregon

16395

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

T 24 S
1/4 S 28
S 33
R 4 W
1963

from which an original bearing tree

A white oak, 33 ins. diam., bears S. 54° E., 668
lks. dist., with fragmentary scribe marks visible on
overgrowth.

and bearing trees mkd. by Godfrey

A white oak, 14 ins. diam., bears N. 52° W., 334 lks. dist.,
with healed blaze.

An ash, 30 ins. diam., bears S. 62° E., 17 1/2 lks. dist.,
with healed blaze.

Corner is located at bottom of descent, slopes S.

S. 89° 50' W., beginning new measurement.

Ascend 300 ft. over E. slope.

39.82 The cor. of secs. 28, 29, 32, and 33.

Land, mountainous
Soil, rocky clay loam.
Timber, fir, hemlock, cedar, maple, oak, madron, myrtle, chinqua-
pin, ash, and alder; undergrowth, salal, vine maple, rhododendron,
poison oak, Oregon grape, and fern.

N. 0° 04' W., bet. secs. 28 and 29.

Descend 65 ft. over NE slope, through scattering timber and
moderate undergrowth.

18.40 Wet ravine, drains S. 40° E.; asc. 15 ft. over S. slope.

20.055 Point for the S 1/16 sec. cor. of secs. 28 and 29.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the
ground, with brass cap mkd.

S 1/16
S 29 | S 28
1979

from which

A fir, 11 ins. diam., bears N. 75° E., 36 1/2 lks. dist.,
mkd. S 1/16 S28 BT.

A fir, 18 ins. diam., bears S. 78° W., 22 lks. dist., mkd.
S 1/16 S29 BT.

Ascend 50 ft. over SE slope

24.20 Spur, slopes S. 40° E., asc. 185 ft. over SE slope, changing to
SW slope.