

County Surveyor's Record, Douglas County, Oregon

16397

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

T 24 S R 4 W

S 20 | S 21

S 29 | S 28

1960

*FD. B.C. 11/92
M. HEMMESER
M 116-12*

from which an original bearing tree

A white oak, 30 ins. diam., bears S. 82° W., 218 lks. dist.,
with decayed blaze, no marks visible.

and bearing trees mkd. by Byron

A fir, 12 ins. diam., bears N. 76 3/4° E., 13 lks., dist.,
with healed blaze.

An oak, 10 ins. diam., bears S. 30° E., 25 1/2 lks. dist.,
with healed blaze.

An oak, 8 ins. diam., bears S. 32° W., 21 lks. dist., with
healed blaze.

An oak, 12 ins. diam., bears N. 43° W., 18 1/2 lks. dist.,
with healed blaze.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, maple, oak, madrone, alder, chinquapin,
and ash; undergrowth, salal, rhododendron, vine maple
poison oak, Oregon grape, and fern.

From the cor. of secs. 9, 10, 15, and 16.

N. 89° 40' W., bet. secs. 9 and 16.

Ascend 5 ft. over E. slope, through scattering timber and dense
undergrowth.

3.50 Ridge, bears N. 45° W. and S. 45° E.; desc. 480 ft. over SW slope.

27.00 Creek, 1 lk. wide, course S. 40° W.; asc. 15 ft. over SE slope.

29.60 Top of ascent, slopes S. 45° W.; desc. 120 ft. over SW slope.

39.86 The 1/4 sec. cor. of secs. 9 and 16, perpetuated and recorded
by Milo E. Godfrey, Deputy County Surveyor, in 1963, monumented
with an iron post, 1 1/4 ins. diam., firmly set, projecting
8 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 24 S

1/4 S 9

S 16

R 4 W

1963

from which an original bearing tree

A maple, 25 ins. diam., bears N. 19° W., 14 lks. dist.,
with open blaze, no marks visible.

and bearing trees mkd. by Godfrey